

Tehničke karakteristike artikla: BK080008--

Uzidna 1-redna tabla, U24, providna vrata

Ugradna razvodna tabla 1-red, 24MV, providna vrata, IP40, V=232 Š=500 D=106mm



SCHRACK-Info

- Uzidni razdjelnik. ABS s prozirnim vratima
- Zatvaranje: tipka/pritisak, mogućnost ugradnje male cilindar brave
- Sadrži PE i N stezaljke
- Klasa zaštite II
- Bez halogena prema RoHS
- Nazivni napon 400V AC / In=63A
- Temperatura okoline: -25° do +60°C
- Ispitivanje na žarnu nit: 650°C
- Ugradna dubina: 68-70mm
- Stupanj zaštite: IP40, Otpornost na udar: IK08
- RAL9010 čista bijela



Tehnički podaci

Neto širina (mm)	498,00
Neto visina (mm)	254,00
Neto dubina (mm)	106,00

Tehnički podaci - nastavak

Neto težina (kg)	1,44
EAN	9004840917017
Gubitak snage (W)	-30,00
Min. temperatura okoline (°C)	-25
Maks. temperatura okoline (°C)	60
Materijal vrata	plastičan providan
Bezhalogeni	Da
Verzija	Ugradni sa vratima
Redovi	1
Modula u 1 redu	24
IP stepen zaštite	IP40
Opis boje	RAL 9003 (bela)

Tabela artikla

OPIS	Kat. broj
Uzidna 1-redna tabla, U24, providna vrata	BK080008
Ugradna razvodna tabla 1-red, 24MV, providna vrata, IP40, V=232 Š=500 D=106mm	
Dodatni pribor	
Brava sa ključem za razvodne table (metal)	BK080096
metal, 2x keys included	