

Tehničke karakteristike artikla: DS428010-B

19" Samost. orman 42U/ 1970x800x1000 (VxŠxD), 400kg, IP20, crni

RAL9005 (crna), staklena vrata, IP20



SCHRACK-Info

TECHNICAL DATA

- The frame, the door, the side panels, the roof plate and the base plate are made of 1.0 mm sheet metal. The mounting for the optional castors is made of 2.0 mm sheet metal. All these parts are made of DC01 quality sheet steel. The vertical rails are made of galvanised sheet metal with a thickness of 2.0mm.
- Welded powder-coated sheet steel skeleton
- Height: 42U
- Width: 800mm
- Depth: 1000mm
- Colour:
 - Black RAL9005.
- Maximum Load:
 - 15-22U: 300kg
 - 27-47U: 400kg
- Degree of protection: IP20
- 4 mm thick safety glass doors with handsome swing handle. Prepared for half-cylinder type locks. Halfcylinder lock (Order-number: DV900333), Depth= 40mm, Diameter= 17mm, Fixing= M5 Screw, optional available.
- Doors hinged right. Can be changed to hinging on left.
- External hinge system allows up to 180 degree door opening angle.
- Glass doors can be replaced by optional DSRT doors (full metal or perforated, full width or double-wing).

- Removeable and lockable side-panels. Key included. For better passive cooling, side-panels can be replaced by optional perforated side-panels DSRS.
- Removeable and lockable rear-panel. Key included. Rear panel can be replaced by optional DSRT doors (glass, full or perforated metal, full width or double-wing) or by perforated rear-panel DSRR.
- 19" rails (4 pcs.) galvanised, continuously depthadjustable. Numbering of Height-Units (U) by laser for easy readability.
- In 800mm wide DS enclosures, you can choose to adjust the 19" rails to a width of 21".
- In 900, 1.000 and 1.200 mm deep DS enclosures, there is an additional pair of vertical rails installed in half depth. This makes installation of high depth accessories together with standard accessories possible at the same time.
- Space between front vertical 19"-rail and door glass at max. spacing:
 - W600 – 35mm
 - W800 – 50mm
- Space between rear vertical 19"-rail and rear panel at max. spacing:
 - W600 – 35mm
 - W800 – 55mm
- Maximum distance between vertical rails (19"-rails) in free-standing cabinets:
 - W600 x D400 – 310mm
 - W600 x D600 – 510mm
 - W600 x D800 – 710mm
 - W600 x D900 – 810mm
 - W600 x D1000 – 910mm
 - W600 x D1200 – 1110mm
 - W800 x D600 – 470mm
 - W800 x D800 – 670mm
 - W800 x D900 – 770mm
 - W800 x D1000 – 870mm
 - W800 x D1200 – 1070mm
- Maximum usable depth in free-standing cabinets when installed e.g. on shelves:
 - D400 – 375mm
 - D600 – 575mm
 - D800 – 775mm
 - D900 – 875mm
 - D1000 – 975mm
 - D1200 – 1175mm
- Spacing between vertical 19"-rails: 451 mm
- Roof construction with opening, 19" punched. Flexible covered by removable plates of different heights to allow installation of fan-units and cable-entry panels. Remaining opening can be closed by use of one these plates.
 - D400 - Opening: 6U, Covering: 1 x 4U and 1 x 2U
 - D600 - Opening: 8U, Covering: 1 x 4U and 2 x 2U
 - D800 - Opening: 10U, Covering: 2 x 4U and 1 x 2U
 - D900 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
 - D1000 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
 - D1200 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
- Floor construction with opening, 19" punched. Covered by removable plate in full height.
 - D400 - Opening: 6U, Covering: 1 x 6U
 - D600 - Opening: 8U, Covering: 1 x 8U
 - D800 - Opening: 10U, Covering: 1 x 10U
 - D900 - Opening: 12U, Covering: 1 x 12U

- D1000 - Opening: 12U, Covering: 1 x 12U
- D1200 - Opening: 12U, Covering: 1 x 12U
- Roof unit assemblies can also be fitted to floor section. Optional base required.
- Cable entry possible via roof, floor and rear panel. Delivered with demountable or break-out blanking plates.
- Brush strip panel for roof (DBK24800) optional.
- Air vents for passive ventilation.
- Earthing:
 - M8-Earthing point plus 19"-Earthingset in the rear of the cabinet
 - FastOn-Earthing-connections to all dismountable parts pre-installed
- Included assembly materials:
 - 16 x Cage nuts, bolts and washers M6
 - 4 x Levelling feet
- Wide range of available accessories (bases, fan-units, cable entry panels, fixed shelves, patch panels, cable management, PDUs, doors, etc.).
- Enclosure is delivered fully-assembled on a disposable pallet.

Tehnički podaci

Neto širina (mm)	800,00
Neto visina (mm)	1.970,00
Neto dubina (mm)	1.000,00
Neto težina (kg)	104,20
Min. temperatura okoline (°C)	0
Maks. temperatura okoline (°C)	40
Prikladno za visinu unit-a	42U-1970mm
Opis boje	RAL 9005 (crna)

Tabela artikla

OPIS	Kat. broj
19"Samost.orman 42U/1970x800x1000 (VxŠxD),400kg,IP20,crni RAL9005 (crna), staklena vrata, IP20	DS428010-B
Dodatni pribor	
Bočne strane podnožja ormana DS dubine 1000mm, 1 SET=2kom,crne RAL9005 (crna), par, h=120mm, za ormane serije DS/DSS	DSOT1210-B
Panel podnožja ormana DS/DSS/DST,Š800mm,slepi,crn RAL9005 (crna),za DS/DSS/DST/DSZ širine 600mm,h=120mm	DSOF1280-B
Umetak polucilindrične brave EK 333 s jednim ključem i M5 1 SET=brava,ključ i vijak M5	DV900333S

Tabela artikla

OPIS	Kat. broj
Dodatni pribor	
Panel sa četkom za podni/krovni uvod kabla, 2U, crni RAL9005 (crna), za ormane DS/DSS/DST/DSZ	DBK24800-B
Krovni panel sa 2 ventilator. i analog.termostat. za DS, crni RAL9005 (crna), za ormane serije DS/DSS/DST	DLT44802-B
19"Ranžirni panel, 5 metalnih prstena 80x40mm, 1U, crni metalni prstenovi, RAL9005 (crna)	DBC14805-B
19"Ranžirni panel, 5 PVC prstena 80x40mm, 1U, crni PVC prstenovi, RAL9005 (crna)	DBK14805-B
19"Polica fiksna, dubine 450mm, 1HU, nosivosti 80kg, crna RAL9005 (crna), montaža u 4 tačke	DFS14845-T
19"Nap.panel 9xSCHUKO, 1HU, ALU, kabl 3m, sivi RAL7035 (svetlo siva)	IU070114-3
19"Nap.panel 7xSCHUKO+PNZ, 1.25HU, PVC, kabl 2m, sivi sa prenaponskom zaštitom T3 (klasa D), RAL7035 (svetlo siva)	IU070113
19"Nap.panel 9xSCHUKO+On/Off, 1HU, ALU, kabl 2m, crni sa On/Off prekidačem, RAL9005 (crna)	Q7070114-A
19"Nap.panel 7xSCHUKO+On/Off+PNZ, 1HU, ALU, kabl 2m, crni sa prenaponskom zaštitom T3 (klasa D), RAL9005 (crna)	Q7070113-A
PDU 12xC13/6xSCHUKO, pasivni, IN:CEE 3-f/16A, ALU, 821mm pasivni PDU, ulaz: IEC CEE 3-f/16A, ALU, 821mm	HSMPP312
Set nosača za vertikalnu montažu PDU, za DS širine 800mm, 1HU 1 SET=2 komada, pocinkovan, za DS širine 800mm	DSPDU010
Set za fiksiranje 19" opreme, M6 (vijak+kavez matica), 50kom 1 SET=50 komada	DSSRA050
Montazna ploča 19", 14HU, 622x482x1mm (VxŠxD), perforirana pocinkovani čelični lim, uključeni vijci i kavez matice	DMP1914
19"LED svetiljka sa prekidačem i senzorom pokreta, 230VAC montaža na 19" šinu (vijkom) ili pomoću magneta	DTLIGHT01
Switch 24xRJ45 10/100/1000, tihi, bez ventilatora, interni Metalno kućište, 19"	QLGSW2457
19"Patch panel 24xRJ45 (SFA, SFB), 1HU, prazan, crni fiksni zadnji nosač kabla, RAL9005 (crna)	HSERO240SP