


Tehničke karakteristike artikla: DSZ426020-

# 19" Samost. orman 42U/ 1970x600x1200(VxŠxD), rasklopiv, IP20, sivi

rasklopiv, RAL7035 (svetlo siva), nosivosti 400kg



## SCHRACK-Info

- Powder-coated sheet steel skeleton 1,5mm
- Height: 42U
- Width: 600mm
- Depth: 1.200mm
- Demountable Parts:
  - Front Part: 105mm
  - Rear Part: 105 mm
- Main Part welded:
  - 390mm at 600 deep enclosure
  - 590mm at 800 deep enclosure
  - 690mm at 900 deep enclosure &lt;/li>
  - 790mm at 1.000 deep enclosure
  - 990mm at 1.200 deep enclosure
- Colour: Light Grey RAL 7035,
- Frame Blue RAL 5005
- Maximum load:
  - 15 – 22U: 300 kg
  - 27 – 47 U: 400kg

- Degree of protection: IP20
- 4 mm thick safety glass doors with handsome swing handle. Prepared for half-cylinder type locks. Halfcylinder lock (Order-number: DV900333), Depth= 40mm, Diameter= 17mm, Fixing= M5 Screw, optional available.
- Doors hinged right. Can be changed to hinging on left .
- External hinge system allows up to 180 degree door opening angle.
- Front glass door can be replaced by optional DSRT metal door (full metal or perforated).
- Removeable and lockable rear and side panels. Key included.
- Rear panel can be replaced by optional DSRT rear door. Glass- or metal door (full metal or perforated). 19" rails (4 pcs.) galvanised, continuously depthadjustable. Numbering of Height-Units (U) by laser for easy readability.
- In 800mm wide DSZ enclosures, you can choose to adjust the 19" rails to a width of 21" .
- In 900, 1.000 and 1.200 mm deep DSZ enclosures there is an additional pair of vertical rails installed in half depth. This makes installation of high depth accessories together with standard accessories at the same time possible.
- Space between front vertical 19"-rail and door glass at max. spacing:
  - W600 – 43mm
  - W800 – 50mm
- Space between rear vertical 19"-rail and rear panel at max. spacing:
  - W600 – 45mm
  - W800 – 55mm
- Maximum distance between vertical rails (19"-rails) in free-standing cabinets:
  - W600 x D600 – 494mm
  - W600 x D800 – 694mm
  - W600 x D900 – 794mm
  - W600 x D1000 – 894mm
  - W600 x D1200 – 1.094mm
  - W800 x D600 – 470mm
  - W800 x D800 – 670mm
  - W800 x D900 – 770mm
  - W800 x D1000 – 870mm
  - W800 x D1200 – 1.070mm
- Maximum usable depth in free-standing cabinets when installed e.g. on shelves:
  - D600 – 575mm
  - D800 – 775mm
  - D900 – 875mm
  - D1000 – 975mm
  - D1200 – 1.175mm
- Spacing between vertical 19"-rails: 451 mm
- Roof construction with 19" punching.
- 600 mm deep DSZ enclosures come with 8U deep roof aperture, flexible covering with 1 x 4U and 2 x 2U cover plates.
- 800 mm deep DSZ enclosures come with 10U deep roof aperture, flexible covering with 2 x 4U and 1 x 2U cover plates.
- 1.000 and 1.200 mm deep DS enclosures come with 12U deep roof aperture, flexible covering with 2 x 4U and 2 x 2U cover plates.
- Floor construction with 19" punching.
- Roof unit assemblies can also be fitted to floor section. Optional base required.
- Cable entry possibility via roof, floor and rear panel. Delivered with blanking plates.
- Brush strip cable entry panel for roof (DBK24800) optional available.
- Air vents for passive ventilation Fully pre-wired earthing.

- Includes M8 earthing point and earthing kit. Including assembly materials: 24 x Cage nuts, bolts and washers M6, 4 x Levelling feet.
- Wide range of available accessories (bases, fan-units, cable entry panels, fixed shelves, patch panels, cable management, PDUs, etc.).
- Enclosure is delivered fully-assembled on a disposable pallet.

## Tehnički podaci

|                                |                                           |
|--------------------------------|-------------------------------------------|
| Neto širina (mm)               | 600,00                                    |
| Neto visina (mm)               | 1.970,00                                  |
| Neto dubina (mm)               | 1.200,00                                  |
| Neto težina (kg)               | 110,80                                    |
| Min. temperatura okoline (°C)  | 0                                         |
| Maks. temperatura okoline (°C) | 40                                        |
| Prikladno za visinu unit-a     | 42U-1970mm                                |
| Opis boje                      | RAL 7035 / RAL 5005 (svetlo siva / plava) |

## Tabela artikla

| OPIS                                                                                                                           | Kat. broj  |
|--------------------------------------------------------------------------------------------------------------------------------|------------|
| 19"Samost.orman 42U/1970x600x1200(VxŠxD),rasklopiv,IP20,sivi<br>rasklopiv, RAL7035 (svetlo siva), nosivosti 400kg              | DSZ426020  |
| <b>Dodatni pribor</b>                                                                                                          |            |
| Umetak polucilindrične brave EK 333 s jednim ključem i M5<br>1 SET=brava,ključ i vijak M5                                      | DV900333S  |
| Panel sa četkom za podni/krovni uvod kabla,2U,sivi<br>RAL7035 (svetlo siva), za ormane DS/DSS/DST/DSZ                          | DBK24800   |
| Krovni panel sa 2 ventilator. i analog.termostat. za DS,sivi<br>RAL7035 (svetlo siva), za ormane serije DS/DSS/DST             | DLT44802-A |
| Bočne strane podnožja ormara DS dubine 1200mm, 1 SET=2kom,sive<br>RAL7035 (svetlo siva), par, h=120mm, za ormane serije DS/DSS | DSOT1220   |
| Panel podnožja ormara DS/DSS/DST,Š600mm,perfor/filter,sivi<br>RAL7035 (svetlo siva), za DS/DSS/DST/DSZ širine 600mm,h=120mm    | DSOF1263   |
| 19"Ranžirni panel,5 metalnih prstena 80x40mm, 1 U,sivi<br>metalni prstenovi, RAL7035 (svetlo siva)                             | DBC14805   |
| 19"Ranžirni panel,5 PVC prstena 80x40mm, 1 U,sivi<br>PVC prstenovi, RAL7035 (svetlo siva)                                      | DBK14805   |
| 19"Polica fiksna,dubine 450mm, 1HU,nosivosti 80kg,siva<br>RAL7035 (svetlo siva), montaža u 4 tačke                             | DFS14845-C |

## Tabela artikla

| OPIS                                                                                                                    | Kat. broj  |
|-------------------------------------------------------------------------------------------------------------------------|------------|
| <b>Dodatni pribor</b>                                                                                                   |            |
| 19" Nap. panel 9xSCHUKO, 1HU, ALU, kabl 3m, sivi<br>RAL7035 (svetlo siva)                                               | IU070114-3 |
| 19" Nap. panel 7xSCHUKO+PNZ, 1.25HU, PVC, kabl 2m, sivi<br>sa prenaponskom zaštitom T3 (klasa D), RAL7035 (svetlo siva) | IU070113   |
| 19" Nap. panel 9xSCHUKO+On/Off, 1HU, ALU, kabl 2m, crni<br>sa On/Off prekidačem, RAL9005 (crna)                         | Q7070114-A |
| 19" Nap. panel 7xSCHUKO+On/Off+PNZ, 1HU, ALU, kabl 2m, crni<br>sa prenaponskom zaštitom T3 (klasa D), RAL9005 (crna)    | Q7070113-A |
| Set za fiksiranje 19" opreme, M6 (vijak+kavez matica), 50kom<br>1 SET=50 komada                                         | DSSRA050   |
| Montazna ploča 19", 14HU, 622x482x1mm (VxŠxD), perforirana<br>pocinkovani čelični lim, uključeni vijci i kavez matice   | DMP1914    |
| 19" LED svetiljka sa prekidačem i senzorom pokreta, 230VAC<br>montaža na 19" šinu (vijkom) ili pomoću magneta           | DTLIGHT01  |
| Switch 24xRJ45 10/100/1000, tihi, bez ventilatora, interni<br>Metalno kućište, 19"                                      | QLGSW2457  |
| 19" Patch panel 24xRJ45 (SFA, SFB), 1HU, prazan, sivi<br>demontažni zadnji nosač kabla, RAL7035 (svetlo siva)           | HSER0240GS |