

Tehničke karakteristike artikla: DSZ428020-

19" Samost. orman 42U/ 1970x800x1200(VxŠxD), rasklopiv, IP20, sivi rasklopiv, RAL7035 (svetlo siva), nosivosti 400kg



SCHRACK-Info

- Powder-coated sheet steel skeleton 1,5mm
- Height: 42U
- Width: 800mm
- Depth: 1.200mm
- Demountable Parts:
 - Front Part: 105mm
 - Rear Part: 105 mm
- Main Part welded:
 - 390mm at 600 deep enclosure
 - 590mm at 800 deep enclosure
 - 690mm at 900 deep enclosure
 - 790mm at 1.000 deep enclosure
 - 990mm at 1.200 deep enclosure
- Colour: Light Grey RAL 7035,
- Frame Blue RAL 5005
- Maximum load:
 - 15 – 22U: 300 kg
 - 27 – 47 U: 400kg

- Degree of protection: IP20
- 4 mm thick safety glass doors with handsome swing handle. Prepared for half-cylinder type locks. Halfcylinder lock (Order-number: DV900333), Depth= 40mm, Diameter= 17mm, Fixing= M5 Screw, optional available.
- Doors hinged right. Can be changed to hinging on left .
- External hinge system allows up to 180 degree door opening angle.
- Front glass door can be replaced by optional DSRT metal door (full metal or perforated).
- Removeable and lockable rear and side panels. Key included.
- Rear panel can be replaced by optional DSRT rear door. Glass- or metal door (full metal or perforated). 19" rails (4 pcs.) galvanised, continuously depthadjustable. Numbering of Height-Units (U) by laser for easy readability.
- In 800mm wide DSZ enclosures, you can choose to adjust the 19" rails to a width of 21" .
- In 900, 1.000 and 1.200 mm deep DSZ enclosures there is an additional pair of vertical rails installed in half depth. This makes installation of high depth accessories together with standard accessories at the same time possible.
- Space between front vertical 19"-rail and door glass at max. spacing:
 - W600 – 43mm
 - W800 – 50mm
- Space between rear vertical 19"-rail and rear panel at max. spacing:
 - W600 – 45mm
 - W800 – 55mm
- Maximum distance between vertical rails (19"-rails) in free-standing cabinets:
 - W600 x D600 – 494mm
 - W600 x D800 – 694mm
 - W600 x D900 – 794mm
 - W600 x D1000 – 894mm
 - W600 x D1200 – 1.094mm
 - W800 x D600 – 470mm
 - W800 x D800 – 670mm
 - W800 x D900 – 770mm
 - W800 x D1000 – 870mm
 - W800 x D1200 – 1.070mm
- Maximum usable depth in free-standing cabinets when installed e.g. on shelves:
 - D600 – 575mm
 - D800 – 775mm
 - D900 – 875mm
 - D1000 – 975mm
 - D1200 – 1.175mm
- Spacing between vertical 19"-rails: 451 mm
- Roof construction with 19" punching.
- 600 mm deep DSZ enclosures come with 8U deep roof aperture, flexible covering with 1 x 4U and 2 x 2U cover plates.
- 800 mm deep DSZ enclosures come with 10U deep roof aperture, flexible covering with 2 x 4U and 1 x 2U cover plates.
- 1.000 and 1.200 mm deep DS enclosures come with 12U deep roof aperture, flexible covering with 2 x 4U and 2 x 2U cover plates.
- Floor construction with 19" punching.
- Roof unit assemblies can also be fitted to floor section. Optional base required.
- Cable entry possibility via roof, floor and rear panel. Delivered with blanking plates.
- Brush strip cable entry panel for roof (DBK24800) optional available.
- Air vents for passive ventilation Fully pre-wired earthing.

- Includes M8 earthing point and earthing kit. Including assembly materials: 24 x Cage nuts, bolts and washers M6, 4 x Levelling feet.
- Wide range of available accessories (bases, fan-units, cable entry panels, fixed shelves, patch panels, cable management, PDUs, etc.).
- Enclosure is delivered fully-assembled on a disposable pallet.

Tehnički podaci

Neto širina (mm)	800,00
Neto visina (mm)	1.970,00
Neto dubina (mm)	1.200,00
Neto težina (kg)	110,80
Min. temperatura okoline (°C)	0
Maks. temperatura okoline (°C)	40
Prikladno za visinu unit-a	42U-1970mm
Opis boje	RAL 7035 / RAL 5005 (svetlo siva / plava)

Tabela artikla

OPIS	Kat. broj
19"Samost.orman 42U/1970x800x1200(VxŠxD),rasklopiv,IP20,sivi rasklopiv, RAL7035 (svetlo siva), nosivosti 400kg	DSZ428020
Dodatni pribor	
Umetak polucilindrične brave EK 333 s jednim ključem i M5 1 SET=brava,ključ i vijak M5	DV900333S
Panel sa četkom za podni/krovni uvod kabla,2U,sivi RAL7035 (svetlo siva), za ormane DS/DSS/DST/DSZ	DBK24800
Krovni panel sa 2 ventilator. i analog.termostat. za DS,sivi RAL7035 (svetlo siva), za ormane serije DS/DSS/DST	DLT44802-A
Bočne strane podnožja ormara DS dubine 1200mm, 1 SET=2kom,sive RAL7035 (svetlo siva), par, h=120mm, za ormane serije DS/DSS	DSOT1220
Panel podnožja ormara DS/DSS/DST,Š800mm,perfor/filter,sivi RAL7035 (svetlo siva), za DS/DSS/DST/DSZ širine 600mm,h=120mm	DSOF1283
19"Ranžirni panel,5 metalnih prstena 80x40mm, 1 U,sivi metalni prstenovi, RAL7035 (svetlo siva)	DBC14805
19"Ranžirni panel,5 PVC prstena 80x40mm, 1 U,sivi PVC prstenovi, RAL7035 (svetlo siva)	DBK14805
19"Polica fiksna,dubine 450mm, 1HU,nosivosti 80kg,siva RAL7035 (svetlo siva), montaža u 4 tačke	DFS14845-C

Tabela artikla

OPIS	Kat. broj
Dodatni pribor	
19" Nap. panel 9xSCHUKO, 1HU, ALU, kabl 3m, sivi RAL7035 (svetlo siva)	IU070114-3
19" Nap. panel 7xSCHUKO+PNZ, 1.25HU, PVC, kabl 2m, sivi sa prenaponskom zaštitom T3 (klasa D), RAL7035 (svetlo siva)	IU070113
19" Nap. panel 9xSCHUKO+On/Off, 1HU, ALU, kabl 2m, crni sa On/Off prekidačem, RAL9005 (crna)	Q7070114-A
19" Nap. panel 7xSCHUKO+On/Off+PNZ, 1HU, ALU, kabl 2m, crni sa prenaponskom zaštitom T3 (klasa D), RAL9005 (crna)	Q7070113-A
Set za fiksiranje 19" opreme, M6 (vijak+kavez matica), 50kom 1 SET=50 komada	DSSRA050
Montazna ploča 19", 14HU, 622x482x1mm (VxŠxD), perforirana pocinkovani čelični lim, uključeni vijci i kavez matice	DMP1914
19" LED svetiljka sa prekidačem i senzorom pokreta, 230VAC montaža na 19" šinu (vijkom) ili pomoću magneta	DTLIGHT01
Switch 24xRJ45 10/100/1000, tihi, bez ventilatora, interni Metalno kućište, 19"	QLGSW2457
19" Patch panel 24xRJ45 (SFA, SFB), 1HU, prazan, sivi demontažni zadnji nosač kabla, RAL7035 (svetlo siva)	HSER0240GS