


Tehničke karakteristike artikla: HLP29CD00F

FO Patch SC/UPC-SC/ APC, OS2, duplex, LSOH, žuti, 0.5m

UPC-APC, LSOH



SCHRACK-Info

Single mode patch cords are used for telecom networks and also used for high speed metropolitan and access network. The single-mode patch cables are equipped with an LSOH jacket. These comply with IEC or EIA-TIA standards. These singlemode enhanced patch cords are terminated with optimized connectors which give optimum optical performance.

FEATURES

- SC/UPC - SC/APC connectors
- Low smoke zero halogen (LSOH) jacket
- 900 µm tight buffer
- Singlemode cabled fiber conforms to ITU-T G.657.A2, IEC 60793-2-50
- Duplex
- REACH, RoHS and SvHC materials compliant

APPLICATIONS


- CATV / Video
- Passive Optical Network PON
- WDM / DWDM
- FTTH
- Data centers
- Supports high speed multi channel video, data and voice services in metropolitan and access networks

- ATM, SONET and WDM

Tehnički podaci

Standard proizvoda	IEC 61300-3-4 / IEC 61300-3-6
Norma kontaktora	IEC 61754
Kombinacija utičnica	SC UPC/SC APC
Dužina Patch kabla (m)	0,50
Vlakno	9/125 μ OS2 singlemode
Spoljni omotač kabla	LSOH
Opis boje	žuto
Prečnik (mm)	2 x 2,2
Gubitak insertacije tipičan (dB)	$\leq 0,25$
Povratni gubitak tipičan (dB)	APC ≥ 60 / UPC ≥ 50
Min. temperatura okoline (°C)	-20
Maks. temperatura okoline (°C)	60
Neto širina (mm)	150,00
Neto visina (mm)	200,00
Neto težina (kg)	0,04

Dimenzija: FO Patch SC/UPC-SC/APC, OS2, duplex, LSOH, žuti, 0.5m



OPIS	Kat. broj
FO Patch SC/UPC-SC/APC, OS2, duplex, LSOH, žuti, 0.5m	HLP29CD00F
UPC-APC, LSOH	