

Tehničke karakteristike artikla: HSATS508EE

SAT Multiswitch 5 IN 8 OUT for Quattro + Quad LNB, incl.

Power supply 12V 1,6A



SCHRACK-Info

Multiswitch HSATS508EE Series 5 - with signal attenuation adjustment – is a device featuring integrated high-frequency components combined with proven mechanical design, offering a well-balanced product with an excellent price-to-performance ratio.

It deliberately omits unnecessary control elements, indicator lights, and buttons.

Thanks to the use of active modules, the series consistently delivers sufficient signal strength.

The multiswitch HSATS508EE Series 5 is compatible with both Quattro and Quad LNBs.

- DVBT2
- Power supply: 12V
- LNB Support: Quattro / Quad
- Ports: Gold-plated F connectors
- Quick Installation

Tehnički podaci

Neto dužina (mm)	173,00
Neto širina (mm)	128,00
Neto visina (mm)	54,00
Neto težina (kg)	0,65

Tehnički podaci - nastavak

Min. temperatura okoline (°C)	-20
Maks. temperatura okoline (°C)	50

Lista fajlova: SAT Multiswitch 5 IN 8 OUT for Quattro + Quad LNB, incl.

Artikelnummer		HSATS508EE	HSATS516EE
Numer Eingänge	SAT/IF	4 (F)	4 (F)
	Terr.	1 (F)	1 (F)
Ausgänge		8 (F)	16 (F)
terr. Verstärker 47 - 862MHz (Attenuator 0 dB... -15dB)		ja	ja
Auswahl LNB/Polarität		18V/22KHZ 13V/22KHz 18V 13V	
Frequenzbereich	SAT/IF	950 - 2200MHz	950 - 2200MHz
	Terr.	47 - 862MHz	47 - 862MHz
Verlust über Teilnehmerausgänge (dB)	SAT/IF @ 950MHz	0dB	-1 dB
	SAT/IF @ 2150MHz	8dB	7dB
	terr. Rec./Out 1-8	8dB	8dB
Alle Werte liegen innerhalb einer Toleranz von	+/- 1,5dB terr. Rec./Out 9-16		8dB
	terr. Rec./Out 17-24		
	terr. Rec./Out 24-32		

OPIS	Kat. broj
SAT Multiswitch 5 IN 8 OUT for Quattro + Quad LNB, incl. Power supply 12V 1,6A	HSATS508EE