

Tehničke karakteristike artikla: HSATWT50S-

SAT set nosača za cev 50 cm, cev debljine 38-60 mm, čelik

vruće pocinčan, dvodijelni



SCHRACK info

Hot-dip galvanized steel wall bracket, 2-part, for the securely attaching a mast tube with a diameter of Ø 38 to 60mm to the wall. Wall distance: 150mm, adjustable by 10cm. Mast tube not included.

TECHNICAL DATA

- Material: Quality steel
- Struts : Flat profile 30 x 5mm
- Surface: hot-dip galvanizing approx. 80
- Wall distance: 500mm, adjustable up to 10cm
- twist-proof: with 2x twist-proof claws
- consisting of: 1x bipod and 1x tripod holder
- suitable for mast tubes : Ø 38 to 60mm

Tehnički podaci

Neto dužina (mm)	520,00
Neto širina (mm)	560,00
Neto visina (mm)	50,00
Neto težina (kg)	3,90
Min. temperatura okoline (°C)	-40
Maks. temperatura okoline (°C)	60

Tabela artikla

OPIS	Kat. broj
SAT set nosača za cev 50 cm, cev debljine 38-60 mm, čelik vruće pocinčan, dvodijelni	HSATWT50S
Dodatni pribor	
SAT stub dužine 2000mm, Ø50mm, bez kape, pocin. čelik 1.5mm	HSATMM20S
SAT stib, dužine 2000mm, prečnik 60mm, sa završnom kapom, 2.0mm	HSATMM20S6
SAT stub dužine 3000mm, Ø50mm, bez kape, pocin. čelik 2.0mm	HSATMM30S
SAT stup d=3m, Ø60mm, sa kapom, pocinkovani čel. 2mm	HSATMM30S6