


Tehničke karakteristike artikla: HSELS043CR

FO Panel DIN, sa 4 vlakna (2dx), SC, OM3, sivi, CLASSIC

RAL7035 (svetlo siva), DIN montaža, SC/UPC duplex, Class C



Tehnički podaci

Neto širina (mm)	126,00
Neto visina (mm)	35,20
Neto dubina (mm)	155,65
Neto težina (kg)	0,59
Vlakno	50/125μ OM3 multimode
Opis boje	RAL 7035 (svetlo siva)
Gubitak insertacije tipičan (dB)	≤0,2
Povratni gubitak tipičan (dB)	≥35
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	70
Broj vlakana	4
Spojnica/konektor	SC

Dimenzija: FO Panel DIN, sa 4 vlakna (2dx), SC, OM3, sivi, CLASSIC



Tabela artikla

OPIS	Kat. broj
FO Panel DIN, sa 4 vlakna (2dx), SC, OM3, sivi, CLASSIC	HSELS043CR
RAL7035 (svetlo siva), DIN montaža, SC/UPC duplex, Class C	
Dodatni pribor	
FO Splice cevčica, dužine 60mm, prozirna	HELSP00011
FO Splice cevčica, dužine 45mm, prozirna	HELSP00010
Alat za čišćenje FO adaptera/konektora "One-Click"(SC, ST, FC)	HSELSZT002
za UPC/APC	
Tester FO signala (sa integrisanim VFL) i RJ45 tester kablova	
PAŽNJA: ovo je izvor svetla Laser klase 2. Nikada ne gledajte u izvor. Uvijek koristite pokrov na VFL portu kad nije u uporabi.	HSELSZT003
Preporučujemo uporabu specijalnih naočala za rad s laserskim izvorima svetla.	
FO Patch SC/UPC-SC/UPC, OM3, duplex, LS0H, aqua, 2m	HLP23CC02F
UPC-UPC, LS0H	

Tabela artikla

OPIS	Kat. broj
Dodatni pribor	
FO Patch SC/UPC-SC/UPC, OM3, duplex, LS0H, aqua, 5m UPC-UPC, LS0H	HLP23CC05F
FO Patch LC/UPC-SC/UPC, OM3, duplex, LS0H, aqua, 2m UPC-UPC, LS0H	HLP23LC02F
FO Patch LC/UPC-SC/UPC, OM3, duplex, LS0H, aqua, 5m UPC-UPC, LS0H	HLP23LC05F
FO Patch ST/UPC-SC/UPC, OM3, duplex, LS0H, aqua, 2m UPC-UPC, LS0H	HLP23TC02F
FO Patch ST/UPC-SC/UPC, OM3, duplex, LS0H, aqua, 5m UPC-UPC, LS0H	HLP23TC05F