


Tehničke karakteristike artikla: HSELS049CR

FO Panel DIN, sa 4 vlakna (2dx), SC, OS2, sivi, CLASSIC

RAL7035 (svetlo siva), DIN montaža, LC/UPC duplex, Class C



Tehnički podaci

Neto širina (mm)	126,00
Neto visina (mm)	35,20
Neto dubina (mm)	155,65
Neto težina (kg)	0,59
Vlakno	9/125 OS2 Singlemode / G.652.D
Opis boje	RAL 7035 (svetlo siva)
Gubitak insertacije tipičan (dB)	≤0,2
Povratni gubitak tipičan (dB)	≥50
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	70
Broj vlakana	4
Spojnicica/konektor	SC

Dimenzija: FO Panel DIN, sa 4 vlakna (2dx), SC, OS2, sivi, CLASSIC



Tabela artikla

OPIS	Kat. broj
FO Panel DIN, sa 4 vlakna (2dx), SC, OS2, sivi, CLASSIC	HSELS049CR
RAL7035 (svetlo siva), DIN montaža, LC/UPC duplex, Class C	
Dodatni pribor	
FO Splice cevčica, dužine 60mm, prozirna	HELSP00011
FO Splice cevčica, dužine 45mm, prozirna	HELSP00010
Alat za čišćenje FO adaptera/konektora "One-Click"(SC, ST, FC) za UPC/APC	HSELSZT002
Tester FO signala (sa integrisanim VFL) i RJ45 tester kablova	
PAŽNJA: ovo je izvor svetla Laser klase 2. Nikada ne gledajte u izvor. Uvijek koristite pokrov na VFL portu kad nije u uporabi.	HSELSZT003
Preporučujemo uporabu specijalnih naočala za rad s laserskim izvorima svetla.	
FO Patch SC/UPC-SC/UPC, OS2, duplex, LS0H, žuti, 2m	
UPC-UPC, LS0H	HLP29CC02F

Tabela artikla

OPIS	Kat. broj
Dodatni pribor	
FO Patch SC/UPC-SC/UPC, OS2, duplex, LS0H, žuti, 5m UPC-UPC, LS0H	HLP29CC05F
FO Patch LC/UPC-SC/UPC, OS2, duplex, LS0H, žuti, 2m UPC-UPC, LS0H	HLP29LC02F
FO Patch LC/UPC-SC/UPC, OS2, duplex, LS0H, žuti, 5m UPC-UPC, LS0H	HLP29LC05F
FO Patch ST/UPC-SC/UPC, OS2, duplex, LS0H, žuti, 2m UPC-UPC, LS0H	HLP29TC02F
FO Patch ST/UPC-SC/UPC, OS2, duplex, LS0H, žuti, 5m UPC-UPC, LS0H	HLP29TC05F
FO Patch SC/UPC-FC/UPC, OS2, duplex, LS0H, žuti, 2m UPC-UPC, LS0H	HLP29CF02F
FO Patch SC/UPC-FC/UPC, OS2, duplex, LS0H, žuti, 5m UPC-UPC, LS0H	HLP29CF05F