


Tehničke karakteristike artikla: HSELS083LR

FO Panel DIN, sa 8 vlakana (4dx), LC, OM3, sivi, CLASSIC

RAL7035 (svetlo siva), DIN montaža, LC/UPC duplex, Class C



Tehnički podaci

Neto širina (mm)	126,00
Neto visina (mm)	35,20
Neto dubina (mm)	155,65
Neto težina (kg)	0,59
Vlakno	50/125μ OM3 multimode
Opis boje	RAL 7035 (svetlo siva)
Gubitak insertacije tipičan (dB)	≤0,2
Povratni gubitak tipičan (dB)	≥35
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	70
Broj vlakana	8
Spojница/konektor	LC

Dimenzija: FO Panel DIN, sa 8 vlakana (4dx), LC, OM3, sivi, CLASSIC



Tabela artikla

OPIS	Kat. broj
FO Panel DIN, sa 8 vlakana (4dx), LC, OM3, sivi, CLASSIC	HSELS083LR
RAL7035 (svetlo siva), DIN montaža, LC/UPC duplex, Class C	
Dodatni pribor	
FO Splice cevčica, dužine 60mm, prozirna	HELSP00011
FO Splice cevčica, dužine 45mm, prozirna	HELSP00010
Alat za čišćenje FO adaptera/konektora "One-Click"(LC, MU) za UPC/APC	HSELSZT001
Tester FO signala (sa integrisanim VFL) i RJ45 tester kabla	
PAŽNJA: ovo je izvor svetla Laser klase 2. Nikada ne gledajte u izvor. Uvijek koristite pokrov na VFL portu kad nije u uporabi.	HSELSZT003
Preporučujemo uporabu specijalnih naočala za rad s laserskim izvorima svetla.	
FO Patch LC/UPC-LC/UPC, OM3, duplex, LS0H, aqua, 2m	HLP23LL02F
UPC-UPC, LS0H	

Tabela artikla

OPIS	Kat. broj
Dodatni pribor	
FO Patch LC/UPC-LC/UPC, OM3, duplex, LS0H, aqua, 5m UPC-UPC, LS0H	HLP23LL05F
FO Patch LC/UPC-SC/UPC, OM3, duplex, LS0H, aqua, 2m UPC-UPC, LS0H	HLP23LC02F
FO Patch LC/UPC-SC/UPC, OM3, duplex, LS0H, aqua, 5m UPC-UPC, LS0H	HLP23LC05F
FO Patch LC/UPC-ST/UPC, OM3, duplex, LS0H, aqua, 2m UPC-UPC, LS0H	HLP23LT02F
FO Patch LC/UPC-ST/UPC, OM3, duplex, LS0H, aqua, 5m UPC-UPC, LS0H	HLP23LT05F