

Tehničke karakteristike artikla: HSELS125TP

FO Splice box 19", 12 vlakna, ST adapteri, 50/125um OM2 ECO

RAL7035, ECO



SCHRACK-Info

Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:
for 24 ST / FC couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland
- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:
Chassis: 1,0mm
Sliding tray: 1,25mm
Frontpanel: 1,4mm
19" holder: 1,5mm

SPLICE-CASSETTES

- For shrink splice protectors
up to 12 fibres: 1 splice-cassette
up to 24 fibers: 2 splice-cassettes

STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

Tehnički podaci

Vlakno	50/125μ OM2 multimode
Opis boje	RAL 7035 (svetlo siva)
Gubitak insertacije tipičan (dB)	< 0,2
Povratni gubitak tipičan (dB)	> 35
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	70
Broj vlakana	12
Neto širina (mm)	480,00
Neto visina (mm)	44,00
Neto težina (kg)	2,53
Neto dubina (mm)	242,00

Tabela artikla

OPIS	Kat. broj
FO Splice box 19", 12 vlakna, ST adapteri, 50/125um OM2 ECO RAL7035, ECO	HSLS125TP
Dodatni pribor	
FO Splice cevčica, za zaštitu spoja, prozirna, dužine 60mm	HELSP00011
FO Splice cevčica, za zaštitu spoja, prozirna, dužine 45mm	HELSP00010