


Tehničke karakteristike artikla: HSELS129CR

FO Panel DIN, sa 12 vlakana (6dx), SC, OS2, sivi, CLASSIC

RAL7035 (svetlo siva), DIN montaža, SC/UPC duplex, Class C



Tehnički podaci

Neto širina (mm)	126,00
Neto visina (mm)	35,20
Neto dubina (mm)	155,65
Neto težina (kg)	0,59
Vlakno	9/125 OS2 Singlemode / G.652.D
Opis boje	RAL 7035 (svetlo siva)
Gubitak insertacije tipičan (dB)	≤0,2
Povratni gubitak tipičan (dB)	≥50
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	70
Broj vlakana	12
Spojnicu/konektor	SC

Dimenzija: FO Panel DIN, sa 12 vlakana (6dx), SC, OS2, sivi, CLASSIC



Tabela artikla

OPIS	Kat. broj
FO Panel DIN, sa 12 vlakana (6dx), SC, OS2, sivi, CLASSIC	HSELS129CR
RAL7035 (svetlo siva), DIN montaža, SC/UPC duplex, Class C	
Dodatni pribor	
FO Splice cevčica, dužine 60mm, prozirna	HELSP00011
FO Splice cevčica, dužine 45mm, prozirna	HELSP00010
Alat za čišćenje FO adaptera/konektora "One-Click"(SC, ST, FC)	HSELSZT002
za UPC/APC	
Tester FO signala (sa integrisanim VFL) i RJ45 tester kablova	
PAŽNJA: ovo je izvor svetla Laser klase 2. Nikada ne gledajte u izvor. Uvijek koristite pokrov na VFL portu kad nije u uporabi.	HSELSZT003
Preporučujemo uporabu specijalnih naočala za rad s laserskim izvorima svetla.	
FO Patch SC/UPC-SC/UPC, OS2, duplex, LS0H, žuti, 2m	HLP29CC02F
UPC-UPC, LS0H	

Tabela artikla

OPIS	Kat. broj
Dodatni pribor	
FO Patch SC/UPC-SC/UPC, OS2, duplex, LS0H, žuti, 5m UPC-UPC, LS0H	HLP29CC05F
FO Patch LC/UPC-SC/UPC, OS2, duplex, LS0H, žuti, 2m UPC-UPC, LS0H	HLP29LC02F
FO Patch LC/UPC-SC/UPC, OS2, duplex, LS0H, žuti, 5m UPC-UPC, LS0H	HLP29LC05F
FO Patch ST/UPC-SC/UPC, OS2, duplex, LS0H, žuti, 2m UPC-UPC, LS0H	HLP29TC02F
FO Patch ST/UPC-SC/UPC, OS2, duplex, LS0H, žuti, 5m UPC-UPC, LS0H	HLP29TC05F
FO Patch SC/UPC-FC/UPC, OS2, duplex, LS0H, žuti, 2m UPC-UPC, LS0H	HLP29CF02F
FO Patch SC/UPC-FC/UPC, OS2, duplex, LS0H, žuti, 5m UPC-UPC, LS0H	HLP29CF05F