

Tehničke karakteristike artikla: HSELS129LP

FO Panel 19", sa 12 vlakana (6dx), LC, OS2, 1HU, sivi, CLASSIC

RAL7035 (svetlo siva), LC/UPC duplex, Class C



SCHRACK info

Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:
for 12 LC Duplex couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland
- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:
Chassis: 1,0mm
Sliding tray: 1,25mm
Frontpanel: 1,4mm
19" holder: 1,5mm

SPLICE-CASSETTES

- For shrink splice protectors
up to 12 fibres: 1 splice-cassette
up to 24 fibers: 2 splice-cassettes

STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

Tehnički podaci

Neto širina (mm)	480,00
Neto visina (mm)	44,00
Neto dubina (mm)	242,00
Neto težina (kg)	2,53
Vlakno	9/125 OS2 Singlemode / G.652.D
Opis boje	RAL 7035 (svetlo siva)
Gubitak insertacije tipičan (dB)	< 0,2
Povratni gubitak tipičan (dB)	> 50
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	70
Broj vlakana	12

Tabela artikla

OPIS	Kat. broj
FO Panel 19", sa 12 vlakana (6dx), LC, OS2, 1HU, sivi, CLASSIC RAL7035 (svetlo siva), LC/UPC duplex, Class C	HSELS129LP
Dodatni pribor	
FO Splice cevčica, dužine 60mm, prozirna	HELSP00011
FO Splice cevčica, dužine 45mm, prozirna	HELSP00010
Alat za čišćenje FO adaptera/konektora "One-Click"(LC, MU) za UPC/APC	HSELSZT001
Tester FO signala (sa integrisanim VFL) i RJ45 tester kabla PAŽNJA: ovo je izvor svetla Laser klase 2. Nikada ne gledajte u izvor. Uvijek koristite pokrov na VFL portu kad nije u uporabi. Preporučujemo uporabu specijalnih naočala za rad s laserskim izvorima svetla.	HSELSZT003
FO Patch LC/UPC-LC/UPC, OS2, duplex, LS0H, žuti, 2m UPC-UPC, LS0H	HLP29LL02F
FO Patch LC/UPC-LC/UPC, OS2, duplex, LS0H, žuti, 5m UPC-UPC, LS0H	HLP29LL05F
FO Patch LC/UPC-SC/UPC, OS2, duplex, LS0H, žuti, 2m UPC-UPC, LS0H	HLP29LC02F

Tabela artikla

OPIS	Kat. broj
Dodatni pribor	
FO Patch LC/UPC-SC/UPC, OS2, duplex, LS0H, žuti, 5m UPC-UPC, LS0H	HLP29LC05F
FO Patch LC/UPC-FC/UPC, OS2, duplex, LS0H, žuti, 2m UPC-UPC, LS0H	HLP29LF02F