


Tehničke karakteristike artikla: HSELS16SLG

FO Panel 19", sa 8xLCdx adaptera singlemode, 1HU, sivi, PREMIUM

RAL7035 (svetlo siva), LC/UPC duplex, bez pigtail-ova



Tehnički podaci

Neto širina (mm)	482,50
Neto visina (mm)	43,60
Neto dubina (mm)	211,50
Neto težina (kg)	2,70
Vlakno	9/125μ OS2 singlemode
Opis boje	RAL 7035 (svetlo siva)
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	70

Dimension drawing



Tabela artikla

OPIS	Kat. broj
FO Panel 19", sa 8xLCdx adaptera singlemode, 1 HU, sivi, PREMIUM RAL7035 (svetlo siva), LC/UPC duplex, bez pigtail-ova	HSELS16SLG
Dodatni pribor	
FO Patch LC/UPC-LC/UPC, OS2, duplex, LS0H, žuti, 2m UPC-UPC, LS0H	HLP29LL02F
FO Patch LC/UPC-LC/UPC, OS2, duplex, LS0H, žuti, 5m UPC-UPC, LS0H	HLP29LL05F
FO Patch LC/UPC-SC/UPC, OS2, duplex, LS0H, žuti, 2m UPC-UPC, LS0H	HLP29LC02F
FO Patch LC/UPC-SC/UPC, OS2, duplex, LS0H, žuti, 5m UPC-UPC, LS0H	HLP29LC05F
FO Patch LC/UPC-FC/UPC, OS2, duplex, LS0H, žuti, 2m UPC-UPC, LS0H	HLP29LF02F