

Tehničke karakteristike artikla: HSELS245CP

FO Splice box 19", 24 vlakna, SC adapteri, 50/125um OM2 ECO

RAL7035, ECO



SCHRACK-Info

Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:
for 12 SC Duplex couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland
- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:
Chassis: 1,0mm
Sliding tray: 1,25mm
Frontpanel: 1,4mm
19" holder: 1,5mm

SPLICE-CASSETTES

- For shrink splice protectors
up to 12 fibres: 1 splice-cassette
up to 24 fibers: 2 splice-cassettes

STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

Tehnički podaci

Neto širina (mm)	480,00
Neto visina (mm)	44,00
Neto dubina (mm)	242,00
Neto težina (kg)	2,53
Opis boje	RAL 7035 (svetlo siva)
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	70
Gubitak insertacije tipičan (dB)	< 0,2
Povratni gubitak tipičan (dB)	> 35
Vlakno	50/125µ OM2 multimode
Broj vlakana	24

Tabela artikla

OPIS	Kat. broj
FO Splice box 19", 24 vlakna, SC adapteri, 50/125µm OM2 ECO RAL7035, ECO	HSELS245CP
Dodatni pribor	
Optička cevčica za zaštitu spoja 60mm	HELSP00011
Optička cevčica za zaštitu spoja 45mm	HELSP00010
FO Patch kabl, duplex, SC/SC, OM2, multimode, 50/125µm, 2m	HLP25CC02F
FO Patch kabl, duplex, SC/SC, OM2, multimode, 50/125µm, 5m	HLP25CC05F
FO Patch kabl, duplex, LC/SC, OM2, multimode, 50/125µm, 2m	HLP25LC02F
FO Patch kabl, duplex, LC/SC, OM2, multimode, 50/125µm, 5m	HLP25LC05F
FO Patch kabl, duplex, ST/SC, OM2, multimode, 50/125µm, 2m	HLP25TC02F
FO Patch kabl, duplex, ST/SC, OM2, multimode, 50/125µm, 5m	HLP25TC05F