


Tehničke karakteristike artikla: HSELS483CP

FO Panel 19", sa 48 vlakana (24dx), SC, OM3, 1HU, sivi, CLASSIC

RAL7035 (svetlo siva), SC/UPC duplex, Class C



Tehnički podaci

Neto širina (mm)	480,00
Neto visina (mm)	44,00
Neto dubina (mm)	242,00
Neto težina (kg)	2,53
Vlakno	50/125μ OM3 multimode
Opis boje	RAL 7035 (svetlo siva)
Gubitak insertacije tipičan (dB)	< 0,2
Povratni gubitak tipičan (dB)	> 35
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	70
Broj vlakana	48

Tabela artikla

OPIS	Kat. broj
FO Panel 19", sa 48 vlakana (24dx), SC, OM3, 1 HU, sivi, CLASSIC RAL7035 (svetlo siva), SC/UPC duplex, Class C	HSELS483CP
Dodatni pribor	
FO Splice cevčica, dužine 60mm, prozirna	HELSP00011
FO Splice cevčica, dužine 45mm, prozirna	HELSP00010
Alat za čišćenje FO adaptera/konektora "One-Click"(SC,ST,FC) za UPC/APC	HSELSZT002
Tester FO signala (sa integrisanim VFL) i RJ45 tester kablova PAŽNJA: ovo je izvor svetla Laser klase 2. Nikada ne gledajte u izvor. Uvijek koristite pokrov na VFL portu kad nije u uporabi. Preporučujemo uporabu specijalnih naočala za rad s laserskim izvorima svetla.	HSELSZT003
FO Patch SC/UPC-SC/UPC, OM3, duplex, LS0H, aqua, 2m UPC-UPC, LS0H	HLP23CC02F
FO Patch SC/UPC-SC/UPC, OM3, duplex, LS0H, aqua, 5m UPC-UPC, LS0H	HLP23CC05F
FO Patch LC/UPC-SC/UPC, OM3, duplex, LS0H, aqua, 2m UPC-UPC, LS0H	HLP23LC02F
FO Patch LC/UPC-SC/UPC, OM3, duplex, LS0H, aqua, 5m UPC-UPC, LS0H	HLP23LC05F
FO Patch ST/UPC-SC/UPC, OM3, duplex, LS0H, aqua, 2m UPC-UPC, LS0H	HLP23TC02F
FO Patch ST/UPC-SC/UPC, OM3, duplex, LS0H, aqua, 5m UPC-UPC, LS0H	HLP23TC05F