

Tehničke karakteristike artikla: IG700301--

Poklopac D-G ŠxVxD 380x280x30 IP67

Polycarbonate



SCHRACK-Info

- Installation enclosure made of impact-resistant GRP-PC (glass-fibre reinforced polycarbonate) with knock-out flange embossing (some dimensions also available with smooth side walls)
- Cover grey or transparent 30 or 80mm high made of PC, cover screws made of polyamide
- Seal Polyurethane, fully insulated, halogen-free
- Temperature range: -40 to 80°C
- Protection class (EN 60529): IP67
- Impact resistance (EN 62262): IK08
- Self-extinguishing: base UL94-V1, cover UL94-V2
- RAL7035 Light grey
- Accessories: mounting plates, flanges, intermediate frame (+50mm) and various cover screws

TECHNICAL DATA

- Material: Polycarbonat
- Design: Installation enclosure
- Protection class: IP67
- Dimensions (DxWxH): 30,00 x 380,00 x 280,00mm
- Weight: 0,47kg
- Cover: grey
- Packaging unity: 1Stk.

Tehnički podaci

Neto širina (mm)	380,00
Neto visina (mm)	280,00
Neto dubina (mm)	30,00
Neto težina (kg)	0,47
IP stepen zaštite	IP67
Materijal	Polikarbonat
Opis boje	RAL 7035
Širina (mm)	280
Visina (mm)	30

Tabela artikla

OPIS	Kat. broj
Poklopac D-G ŠxVxD 380x280x30 IP67	IG700301
Polycarbonate	
Dodatni pribor	
Postolje D1 ŠxVxD 380x280x100 IP67	IG700302
Polycarbonate	
Postolje DY4 ŠxVxD 380x280x150 IP67	IG700602
Polycarbonate	
Zavrtnj sa razrezom 30 mm	IG713028
Leptirasti zavrtnj 80 mm	IG713026