

Tehničke karakteristike artikla: IG700302--

Postolje D1 ŠxVxD 380x280x100 IP67

Polycarbonate



SCHRACK-Info

- Installation enclosure made of impact-resistant GRP-PC (glass-fibre reinforced polycarbonate) with knock-out flange embossing (some dimensions also available with smooth side walls)
- Cover grey or transparent 30 or 80mm high made of PC, cover screws made of polyamide
- Seal Polyurethane, fully insulated, halogen-free
- Temperature range: -40 to 80°C
- Protection class (EN 60529): IP67
- Impact resistance (EN 62262): IK08
- Self-extinguishing: base UL94-V1, cover UL94-V2
- RAL7035 Light grey
- Accessories: mounting plates, flanges, intermediate frame (+50mm) and various cover screws

TECHNICAL DATA

- Material: GFK Polycarbonat
- Design: Installation enclosure
- Protection class: IP67
- Dimensions (DxWxH): 100,00 x 380,00 x 280,00mm
- Weight: 1,19kg
- Colour: RAL 7035
- Packaging unity: 1Stk.

Tehnički podaci

Neto širina (mm)	380,00
Neto visina (mm)	280,00
Neto dubina (mm)	100,00
Neto težina (kg)	1,19
IP stepen zaštite	IP67
Materijal	GFK polikarbonat
Opis boje	RAL 7035
Širina (mm)	280
Visina (mm)	100

Dimenzija: Postolje D1 ŠxVxD 380x280x100 IP67




Tabela artikla

OPIS	Kat. broj
Postolje D1 ŠxVxD 380x280x100 IP67	IG700302
Polycarbonate	
Dodatni pribor	
Poklopac D-G ŠxVxD 380x280x30 IP67	IG700301
Polycarbonate	
Poklopac D-D ŠxVxD 380x280x30 IP67	IG700311
Polycarbonate	
Poklopac D-GH 380x280x80 IP 67	IG700321
Polycarbonate	
Poklopac D-DH 380x280x80 sivi	IG700331
Polycarbonate	
Montazna ploca za kućište D-338x248 suitable for IG700904-- , IG700302-- and IG700602--	IG710302

Tabela artikla

OPIS	Kat. broj
Dodatni pribor	
Medjuokvir za kućište D-380x280 suitable for IG700904-- , IG700302-- and IG700602--	IG710301
Kablovski uvodnik KII-260	IG712516
Kablovski uvodnik KII-160	IG712512
Prirubnica II-2xM20 + 5xM25/16	IG712211
Prirubnica II-slepa	IG712200
Komplet dihtunga II Each 4x screws, 4x plates, 4x tooth washers, 4x nuts	IG713003
Klinasti šarnir komplet	IG713001