

Tehničke karakteristike artikla: IG700331--

Poklopac D-DH 380x280x80 sivi

Polycarbonate



SCHRACK-Info

- Installation enclosure made of impact-resistant GRP-PC (glass-fibre reinforced polycarbonate) with knock-out flange embossing (some dimensions also available with smooth side walls)
- Cover grey or transparent 30 or 80mm high made of PC, cover screws made of polyamide
- Seal Polyurethane, fully insulated, halogen-free
- Temperature range: -40 to 80°C
- Protection class (EN 60529): IP67
- Impact resistance (EN 62262): IK08
- Self-extinguishing: base UL94-V1, cover UL94-V2
- RAL7035 Light grey
- Accessories: mounting plates, flanges, intermediate frame (+50mm) and various cover screws

TECHNICAL DATA

- Material: Polycarbonat
- Design: Installation enclosure
- Protection class: IP67
- Dimensions (DxWxH): 80,00 x 380,00 x 280,00mm
- Weight: 0,74kg
- Cover: grey
- Packaging unity: 1Stk.

Tehnički podaci

Neto širina (mm)	380,00
Neto visina (mm)	280,00
Neto dubina (mm)	80,00
Neto težina (kg)	0,74
IP stepen zaštite	IP67
Materijal	Polikarbonat
Širina (mm)	280
Visina (mm)	80

Tabela artikla

OPIS	Kat. broj
Poklopac D-DH 380x280x80 sivi Polycarbonate	IG700331
Dodatni pribor	
Postolje D1 ŠxVxD 380x280x100 IP67 Polycarbonate	IG700302
Postolje DY4 ŠxVxD 380x280x150 IP67 Polycarbonate	IG700602
Postolje 380x280x100 bez prirubnice IP67 Poklopac kućišta naručiti odvojeno.	IG700904
Leptirasti zavrtnj 30 mm	IG713025
Zavrtnj sa razrezom 80 mm	IG713029