


Tehničke karakteristike artikla: IL153428GS

# Masken-Zählerverteiler 4M-28E/STMK 4ZP, H1335B980T200mm

4 Mesta za brojila, 1 Redova brojila, 4 Downstream redovi, 180 Širine modula, Pokrovnna ploča metal, Štajerska



## SCHRACK-Info

- Modular aufgebauter Maskenverteiler mit PVC-Rückwand ohne Tür
- Material: 1 mm pulverbeschichtetes Stahlblech
- Phosphatierter, kunststoffpulverbeschichteter Stahlblechverteiler geprüft und zertifiziert nach EN 62208:2011 und EN 60529:1991, Schutzklasse I für TT/TN und IT Netzform geeignet, schutzisoliert nach ÖVE-IM 12
- Die Ausführung des Vorzählerteils besteht aus einer Vorzähler-Türe mit Ausprägung für EVU-Schlosseinbau und Ausschnitt für Vorzählersicherungsautomaten inklusive montierter Hutschiene
- Bemessungsspannung Ue: 230/400V/50Hz
- Bemessungsisolationsspannung Ui: 1000V
- Bemessungsstoßspannungsfestigkeit Uimp: 6kV
- Bemessungskurzzeitstromfestigkeit Icw: 25kA / 1s
- Bemessungsstoßstromfestigkeit Ipk: 54kA
- Bedingter Bemessungskurzschlussstrom Icc: 25kA
- Schutzklasse: I
- EMV: EMV Umgebung 1
- komplett bestückt und vorverdrahtet auf Anfrage



## Tehnički podaci

|                   |                                               |
|-------------------|-----------------------------------------------|
| Neto širina (mm)  | 980,00                                        |
| Neto visina (mm)  | 1.335,00                                      |
| Neto dubina (mm)  | 200,00                                        |
| EAN               | 9004840635546                                 |
| Gubitak snage (W) | -498,00                                       |
| Tip               | Maskirna razvodna tabla sa brojiлом (komplet) |
| Regija            | Štajerska                                     |
| Umeci             | Prednje maske metalne                         |
| Opis boje         | RAL 7035                                      |
| Širina brojila    | 4                                             |
| Visina unit-a     | 28                                            |
| Redova brojila    | 1                                             |
| Mesta za brojila  | 4                                             |
| IP stepen zaštite | IP20C                                         |
| Downstream redovi | 4                                             |
| Pokrovna ploča    | metal                                         |
| Osnovni opis      | Kućište                                       |
| Širine modula     | 180                                           |

## Tabela artikla

| OPIS                                                                                                                                                                                                                                                                                                                                                           | MASA BAKRA (kg/km) | Kat. broj  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|------------|
| Masken-Zählerverteiler 4M-28E/STMK 4ZP, H1335B980T200mm<br>4 Mesta za brojila, 1 Redova brojila, 4 Downstream redovi, 180 Širine modula, Pokrovna ploča metal, Štajerska                                                                                                                                                                                       |                    | IL153428GS |
| <b>Dodatni pribor</b>                                                                                                                                                                                                                                                                                                                                          |                    |            |
| Podnožje dubine 200mm razdelnika za 0 (1 par)                                                                                                                                                                                                                                                                                                                  |                    | IL091120   |
| Podnožje širine 4 razdelnika za                                                                                                                                                                                                                                                                                                                                |                    | IL091040   |
| Samol. natpisna folija sa piktogramima, 1m                                                                                                                                                                                                                                                                                                                     |                    | BK002401   |
| Pokrivna traka, slepa, 1000x50x8mm, glatka, RAL7035<br>pokrov praznih mjesta u razdjelniku, skraćivanje po potrebi                                                                                                                                                                                                                                             |                    | IL900251   |
| Plug-in counter bar 50A for Vienna, Tyrol and Styria<br>Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm <sup>2</sup> , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019         |                    | IL900189   |
| Plug-in counter bar 50A, PU = 64 Pieces<br>Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm <sup>2</sup> , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019                      |                    | IL900189-A |
| Plug-in counter bar pins 63A, 44mm, PU=7 pieces                                                                                                                                                                                                                                                                                                                |                    | IL900190   |
| Cover for Plug-in counter bars                                                                                                                                                                                                                                                                                                                                 |                    | IL900191   |
| Meter Connection Terminal 50A for Czech Republic, wired 1,3m<br>Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm <sup>2</sup> , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019 | 975                | IL901816   |
| Meter Connection Terminal 50A for Czech Republic, wired 1,8m<br>Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm <sup>2</sup> , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019 | 1350               | IL901820   |
| Meter Connection Terminal 50A for Czech Republic, wired 2,3m<br>Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm <sup>2</sup> , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019 | 1725               | IL901824   |