


Tehničke karakteristike artikla: IL166328WS

Unterputz-Zählerverteiler 3U-28G/WIEN 6ZP, H1380B810T250mm

6 Mesta za brojila, 2 Redova brojila, 1 Downstream redovi, 33 Širine modula, Pokrovnna ploča metal, Beč



SCHRACK-Info

- Modular aufgebauter Unterputzverteiler mit Tür und Mauerwanne
- Material: 1 mm pulverbeschichtetes Stahlblech
- Phosphatierter, kunststoffpulverbeschichteter Stahlblechverteiler geprüft und zertifiziert nach EN 62208:2011 und EN 60529:1991, Schutzklasse I für TT/TN und IT Netzform geeignet, schutzisoliert nach ÖVE-IM 12
- Standardmäßig mit einem Kunststoff-Drehriegelverschluss mit Doppelbartsperr. Beim IL308524-F und ab 28 Modulhöhen sind 2 Drehriegel pro Tür ausgeführt
- Die Ausführung des Vorzählerteils besteht aus einer Gerätefrontplatte mit 45mm Geräteausschnitt oder einer plombierbaren Abdeckung mit montierter Alu/HC Schiene oder SHC-Schiene
- Bemessungsspannung U_e : 230/400V/50Hz
- Bemessungsisolationsspannung U_i : 1000V
- Bemessungsstoßspannungsfestigkeit U_{imp} : 6kV
- Bemessungs kurzzeitstromfestigkeit I_{cw} : 25kA / 1s
- Bemessungsstoßstromfestigkeit I_{pk} : 54kA
- Bedingter Bemessungs kurzschlussstrom I_{cc} : 25kA
- Schutzklasse: I
- EMV: EMV Umgebung 1
- Farbe: RAL9016 (Verkehrsweiß) • komplett bestückt und vorverdrahtet auf Anfrage



Tehnički podaci

Neto širina (mm)	810,00
Neto visina (mm)	1.380,00
Neto dubina (mm)	250,00
EAN	9004840630626
Gubitak snage (W)	-395,00
Tip	Uzidna razvodna tabla sa umetkom za brojila (komplet)
Regija	Beč
Umeci	Prednje maske metalne
Opis boje	RAL 9016
Širina brojila	3
Visina unit-a	28
Redova brojila	2
Mesta za brojila	6
IP stepen zaštite	IP20C
Downstream redovi	1
Pokrovna ploča	metal
Osnovni opis	Kućište
Širine modula	33

Tabela artikla

OPIS	MASA BAKRA (kg/km)	Kat. broj
Unterputz-Zählerverteiler 3U-28G/WIEN 6ZP, H1380B810T250mm 6 Mesta za brojila, 2 Redova brojila, 1 Downstream redovi, 33 Širine modula, Pokrovnna ploča metal, Beč		IL166328WS
Dodatni pribor		
Brava 61005 sa ključem s jednim ključem		IL900200-F
Samol. natpisna folija sa piktogramima, 1 m		BK002401
Pokrivna traka, slepa, 1000x50x8mm, glatka, RAL7035 pokrov praznih mesta u razdjelniku, skraćivanje po potrebi		IL900251
Vertikalni spojni nosači sa konektorima i šrafovim M5x12 2 kom. nosača i 4 kom. M5x12 vijaka		IL369001
Metalni Z instalacioni cilindar sa dva ključa s dva ključa		IL900201-F
Plug-in counter bar 50A for Vienna, Tyrol and Styria Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm ² , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019		IL900189
Plug-in counter bar 50A, PU = 64 Pieces Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm ² , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019		IL900189-A
Plug-in counter bar pins 63A, 44mm, PU=7 pieces		IL900190
Cover for Plug-in counter bars		IL900191
Meter Connection Terminal 50A for Czech Republic, wired 1,3m Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm ² , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019	975	IL901816
Meter Connection Terminal 50A for Czech Republic, wired 1,8m Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm ² , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019	1350	IL901820
Meter Connection Terminal 50A for Czech Republic, wired 2,3m Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm ² , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019	1725	IL901824