

Tehničke karakteristike artikla: ILT40800-A

Izvodno polje 800A, 1042mm, 50x10 busbar system



SCHRACK-Info

- **General** : Type-tested Modul 2000TT outgoing fields for HRC in-line fuse switches up to 630A
- **Material** :
 - Corpus: 1.5mm galvanised sheet steel
 - Doors: Single door and double door: 1.5mm sheet steel
- **Door** :
 - Made of sheet steel and equipped with M8 threaded bolts for earthing. Enclosures in widths 602mm and 822mm are single door versions, enclosures in widths 1042mm and 1242mm are double door versions
 - On single door enclosures, the door is mounted on three double-sided hinges for right-hand opening (=hinged right). On double door enclosures, hinges are not reversible, the left door wing is locked separately with an inner three-point lock
- **Lock** : Three-point rod lock with swing handle (without lock insert), does not slide inward. The standard lock can be exchanged for profile half cylinders (DIN cylinders) from the range of accessories. Double doors are designed with a left-side inner pivot lever
- **Roof** :
 - Two cut-outs for cable entries at widths 602mm and 822mm, three cut-outs at width 1042mm and four cut-outs at width 1242mm
 - Gland plates from our accessories are required for completion
- **Side cut-out** : Contacting possibility for the main busbar. 1 PU (=2 pieces) side covers **IL920001** per enclosure is necessary
- **Baying kit** : A baying kit for baying a second Modul 2000TT enclosure is included
- **Plinth** : 100mm high with cable entry options on the sides. Optionally it is possible to stack two 100mm high plinths on top of each other

- **Protection class** : I
- **Degree of protection** : Standard IP31 up to 1250A, without door it's possible up to 1600A, with corresponding components from our accessories (exhaust filter, gland plates and plinths) IP54 is possible up to 1250A
- **Impact resistance** : IK10
- **Finish** : Textured powder coating
- **Color** : RAL 7035 (Light grey)
- **Delivery includes** :
 - Enclosure with plinth
 - Door with earthing studs
 - Main busbar system
 - Transparent polycarbonate covers
 - Transport connection for main busbar system
 - Baying kit for one more enclosure

Delivered on an Euro-pallet



Tehnički podaci

Neto širina (mm)	1.042,00
Neto visina (mm)	2.140,00
Neto dubina (mm)	400,00
Neto težina (kg)	220,00
Min. temperatura okoline (°C)	-5
Maks. temperatura okoline (°C)	40
IP stepen zaštite	IP31
Materijal	metal
Opis boje	RAL 7035
Širina (mm)	1042
Visina (mm)	2138
Dubina (mm)	400
Gubitak snage (W)	-1009,00
ŠxVxD mm	1042x2140x400
EAN	9004840837261

OPIS	MASA BAKRA (kg/km)	Kat. broj
Izvodno polje 800A, 1042mm, 50x10 busbar system		ILT40800-A

Potreban pribor

Tabela artikla

OPIS	MASA BAKRA (kg/km)	Kat. broj
Potreban pribor		
Poklopac za Modul 2000TT		IL920001
Ploča uvodnice za kablove (slepa), IP66		IL958001-A
Ploča uvodnice za kablove, IP55, 9xØ3-20, 1xØ3-40, 2xØ3-70mm penasta guma		IL958007-A
Ploča uvodnice za kablove, 4xM16, 6xM25/16, 8xM32/20		IL958002-A
Ploča uvodnice za kabl 2xM20, 8xM25/16, 4xM32/20, 1xM50/32 IP66		IL958003-A
Ploča uvodnice za kabl 2xM16, 12xM20, 2xM40/25, 2xM50/32 IP66		IL958004-A
Ploča uvodnice za kablove, IP66, 24xM16, 13xM20		IL958005-A
Ploča uvodnice za kablove, IP55, 44xØ3-14, 3xØ3-21, 2xØ3-30mm penasta guma		IL958006-A
Dodatni pribor		
Modularna maska kpl. 4-42K za NV pruge		ILTAK442
Letva, ARROWLINE, vel.00/3P/160A,M8,na sistem 100mm NH-Leiste, für 100mm-Sammelschienensystem, M8, 3-polig	420	ISA05261
Dvostruki adapter 100/185mm vel.00 Series ARROW-LINE	469	ISA05326
Umetak za nivelisanje pruga vel. 00, 1, 2, 3, 1 pak=2 kom. za prilagođavanje zaslonima vel. 1-3		ISA05329
Rastavna letva, ARROWLINE, vel.1/3P/250A,M10,na sistem 185mm Arrow Line	1943	ISA05305
Rastavna letva, ARROWLINE, vel.2/3P/400A, M12 Arrow Line	1952	ISA05311
Rastavna letva, ARROWLINE, vel.3/3P/630A, M12 Arrow Line	2662	ISA05320
Rastavna letva, ARROWLINE, vel.1/3P/250A, M10, V stezaljka Arrow Line	1965	ISA05306
Rastavna letva, ARROWLINE, vel.2/3P/400A, V stezaljka Arrow Line	1965	ISA05312
Rastavna letva ARROW LINE vel.3, 3P, za 185 mm, V-stezaljke Arrow Line	2685	ISA05321
ARROW rastavna letva sa mestom za ST 160A, veličine 00, 100mm montaža isključivo sa strujnim mjernim transformatorom	391	ISA05340
ARROW rastavna letva sa mestom za ST 250A, veličine 1, 185mm Version to integrate current transformers	1948	ISA05341

Tabela artikla

OPIS	MASA BAKRA (kg/km)	Kat. broj
Dodatni pribor		
HRC-ARROW LINE NV2, 3p, 185mm,V-klema Version to integrate current transformers	1948	ISA05342
HRC-ARROW LINE NV3, 3p, 185mm,V-klema Version to integrate current transformers	2633	ISA05343
Poklopac priključaka za gornju ili donju montažu ARROW 1-3 Za pruge serije ARROW II		ISA05334
Poklopci za prazna polja između ARROW LINE letvi, širine 50mm For the cover for prefabricated cutouts for HRC inline fuses ARROW-LINE in the 185mm busbar system		ISA05356
Poklopci za prazna polja između ARROW LINE letvi, Š 100mm For the cover for prefabricated cutouts for HRC inline fuses ARROW-LINE in the 185mm busbar system		ISA05357
Polucilindar sa dvostrukim zarezom, 5mm, L=40mm		IU001906
Izlazni filter 252X252X38 IP54 for IUKNF4523A, IUKNF5523A		IUKNE450
Prednja maska podnožja 4A../.IP31		IL957400
Podnožje po dubini 400mm, par, IP31 inklusive Schrauben, Ausschnitt 290x50mm		IL090140
Prednja ploča 4B18, čelična ploča with cutout for NH fuse switch		ILT56418-A
Džep za dokumentaciju, samolepljivi, A4		ASDRA400
Transportne ušice M12 za AC/KC za podizanje kompaktnog samostojećeg ili jednog serijskog ormara		ACLE9301
Plombirni pokrivna ploča + 4 sigurnosna umetka u isporuci: 2 trake + 4 pričvrsnice, ne može se ukloniti s prednje strane		IL900112-F