

Tehničke karakteristike artikla: IU070112--

19" Nap.panel 6xSCHUKO+RCBO (BO217516), 1HU, ALU, kabl 2m, siv

kabel s utikačem 3m, RAL7035



SCHRACK info

Sockets:

- 6x CEE 7/3 (Type F)
- DIN 49440, eximinated: VDE0620-1;
- 2-pole with earthing contact;
- 16A/3680W, AC250V, IP20;
- colour similar RAL9005, 35° turned

Connection:

- non rewireable, Endcaps riveted, inside wiring without euro terminal
- 2,0m H05VV-F 3G1,5mm² black with right angled plug with earthing contact

Profile:

- 1U, ALU anodised
- Length: 438,5mm

Plastic material:

- RAL9005, PA6, fibre glass 30%, Glow wire test up to 850°C; V1

Schalter:

- 2-polig, green illuminated

Extent of delivery:

- 1x Socket outlet
- 2x Mounting brackets

Overcurrent protection with residual current circuit breaker (RCBO):

- Rated voltage: 230V~
- Rated current: 16A
- Rated residual current: $\leq 30\text{mA}$
- Pole number: 2
- Tripping characteristic: C
- RCD type: AC
- RCD construction type: G (short-time delayed)

Tehnički podaci

Neto širina (mm)	483,00
Neto visina (mm)	44,00
Neto dubina (mm)	60,00
Neto težina (kg)	1,00
Min. temperatura okoline (°C)	5
Maks. temperatura okoline (°C)	45
Opis boje	RAL 7035 (svetlo siva)

Tabela artikla

OPIS	Kat. broj
19" Nap.panel 6xSCHUKO+RCBO (BO217516), 1HU, ALU,kabl 2m,siv kabel s utikačem 3m, RAL7035	IU070112
Dodatni pribor	
Set nosača za vertikalnu montažu PDU, za DS širine 800mm, 1U 1 SET=2 komada, pocinkovan	DSPDU010
Set nosača za vertikalnu montažu PDU, za ormane DSS/DST, 1HU 1 SET=2 komada, pocinkovan, za ormane DSS/DST širine 800mm	DSSPDU010
Set nosača za vertikalnu montažu PDU, za ormane DSS/DST, 2HU 1 SET=2 komada, pocinkovan, za ormane DSS/DST širine 800mm	DSSPDU021
Napojni kabl SCHUKO/male-C13/male, crni, dužina 1.8m	Q7130121
Napojni kabl SCHUKO/male-C13/male, crni, dužina 3.0m	Q7130059
Napojni kabl SCHUKO/male-C13/male 90°, crni, dužina 5.0m	Q7170732
Napojni kabl Euro-Euro 8, crni, dužina 1.8m	Q7172506
Napojni kabl SCHUKO/male-C5/male, crni, dužina 1.8m	Q7172902