






Tehničke karakteristike artikla: LI151971 --

DOWNUNDER II ugradna lampa 13WG24 D1



Tehnički podaci

Klasa zaštite	I
Vrsta svetiljke (prema načinu primene)	svetiljke za ugradnju u zid Plafonska svetiljka ugradna
Izvor svetla	Fluokompaktna sijalica
Broj svetiljki	1
Sijalično grlo	G24d-1
Snaga (W)	13
Nazivni napon AC (V)	230
Način montaže	Zidno ugradno Plafonska ugradna

Tehnički podaci - nastavak

Otvor (mm)	285x210
Ugradna dubina (mm)	90
Opis boje	Alu
Materijal	Aluminijum
Širina (mm)	221
Visina (mm)	305
Dodatni pribor	LI5V025681; LI5V010625; LI925250--
OTVOR mm	285x210

Tabela artikla

OPIS	Kat. broj
DOWNUNDER II ugradna lampa 13WG24 D1	LI151971
Dodatni pribor	
Fluo sijalica TC-D 10W/3000K G24D-1	LI5V025681
Radium Kompaktleuchtstofflampe Ralux® Duo RX-D 10W/830/G24D	
Fluo sijalica TC-D 13W/4000K G24D-1	LI5V010625
Radium Kompaktleuchtstofflampe Ralux® Duo RX-D 13W/840/G24D	
Ugradni ram za Downunder II&III	LI925250