


Tehničke karakteristike artikla: LI99001704


SERM LED 112 L 1x42W 4000K, 5100lm

Linijska svetiljka, ECG

Ugradna svetiljka za gips plafon, sa nosačima, bele boje



Kriva prostiranja svetla



Tehnički podaci

Neto dužina (mm)	1.500,00
Neto širina (mm)	112,00
Neto visina (mm)	61,00
Neto težina (kg)	2,80
Min. temperatura okoline (°C)	-20
Maks. temperatura okoline (°C)	35
Otvor (mm)	100x1480
Vrsta izvora	Plafonska svetiljka ugradna

Tehnički podaci - nastavak

Montaža	Plafonsko ugradno
Boja	RAL 9003 (bela)
Materijal	metal
Proizvođač	01-Schrack-Trinity
Faktor odsjaja (UGR)	<19
Pogonski uređaj	EVG
Nazivni napon AC (V)	220-240
Grlo	LED Platine
Snaga (W)	37
Sistemska efikasnost (lm/W)	137
Boja svetla	Neutralno bela
Temperatura boje (K)	4000
Indeks reprodukcije boje	≥80
Lumen (lm)	5100
Životni vek	100.000h / L90 / B10
Dimabilno	ne
Klasa zaštite	I
IP stepen zaštite	IP20
Sijalica uključena	da
DxŠxV mm	1500x112x61
OTVOR mm	100x1480

Tabela artikla

OPIS	Kat. broj
SERM LED 112 L 1x42W 4000K, 5100lm Linijska svetiljka, ECG	LI99001704
Ugradna svetiljka za gips plafon, sa nosačima, bele boje	