

Tehničke karakteristike artikla: LI99001707


SERM LED 112 L 1x56W 3000K, 6400lm

Linijaska svetiljka, ECG

Ugradna svetiljka za gips plafon, sa nosačima, bele boje



Kriva prostiranja svetla



Tehnički podaci

Neto dužina (mm)	1.500,00
Neto širina (mm)	112,00
Neto visina (mm)	61,00
Neto težina (kg)	2,80
Min. temperatura okoline (°C)	-20
Maks. temperatura okoline (°C)	35
Otvor (mm)	100x1480
Vrsta izvora	Plafonska svetiljka ugradna

Tehnički podaci - nastavak

Montaža	Plafonsko ugradno
Boja	RAL 9003 (bela)
Materijal	metal
Proizvođač	01-Schrack-Trinity
Faktor odsjaja (UGR)	<20
Pogonski uređaj	EVG
Nazivni napon AC (V)	220-240
Grlo	LED Platine
Snaga (W)	48
Sistemska efikasnost (lm/W)	133
Boja svetla	toplo bela
Temperatura boje (K)	3000
Indeks reprodukcije boje	≥80
Lumen (lm)	6250
Životni vek	100.000h / L90 / B10
Dimabilno	ne
Klasa zaštite	I
IP stepen zaštite	IP20
Sijalica uključena	da
DxŠxV mm	1500x112x61
OTVOR mm	100x1480

Tabela artikla

OPIS	Kat. broj
SERM LED 112 L 1x56W 3000K, 6400lm Linijska svetiljka, ECG	LI99001707
Ugradna svetiljka za gips plafon, sa nosačima, bele boje	