

Tehničke karakteristike artikla: LI99001710


SERM LED 112 M 1x49W 4000K, 5750lm

Linijaska svetiljka, DALI

Ugradna svetiljka za gips plafon, sa nosačima, bele boje



Kriva prostiranja svetla



Tehnički podaci

Neto dužina (mm)	1.200,00
Neto širina (mm)	112,00
Neto visina (mm)	61,00
Neto težina (kg)	2,30
Min. temperatura okoline (°C)	-20
Maks. temperatura okoline (°C)	35
Otvor (mm)	100x1180
Vrsta izvora	Plafonska svetiljka ugradna

Tehnički podaci - nastavak

Montaža	Plafonsko ugradno
Boja	RAL 9003 (bela)
Materijal	metal
Proizvođač	01-Schrack-Trinity
Faktor odsjaja (UGR)	<19
Pogonski uređaj	EVG DALI
Nazivni napon AC (V)	220-240
Grlo	LED Platine
Snaga (W)	31
Sistemska efikasnost (lm/W)	117
Boja svetla	Neutralno bela
Temperatura boje (K)	4000
Indeks reprodukcije boje	≥80
Lumen (lm)	4200
Životni vek	100.000h / L90 / B10
Dimabilno	DALI
Klasa zaštite	I
IP stepen zaštite	IP20
Sijalica uključena	da
DxŠxV mm	1200x112x61
OTVOR mm	100x1180

Tabela artikla

OPIS	Kat. broj
SERM LED 112 M 1x49W 4000K, 5750lm Linijska svetiljka, DALI	LI99001710
Ugradna svetiljka za gips plafon, sa nosačima, bele boje	