

Tehničke karakteristike artikla: LID11048--

Pinta-A MR16 Spot ugaona GU5,3, 50W, IP20, pokretna, bela €ECONOMY

podesivo




Tehnički podaci

Dimabilno	U zavisnosti od izvora svetla Da
Klasa zaštite	III
IP stepen zaštite	IP20
Vrsta svetiljke (prema načinu primene)	svetiljke za ugradnju u zid Plafonska svetiljka ugradna
Izvor svetla	Niskonaponska halogena reflektorska sijalica LED Retrofit
Broj svetiljki	1
Sijalično grlo	GU5,3
Snaga (W)	50
Nazivni napon AC (V)	12
Nazivni napon DC (V)	12

Tehnički podaci - nastavak

Način montaže	Zidno ugradno Plafonska ugradna
Otvor (mm)	Ø75
Ugradna dubina (mm)	65
Opis boje	bela
Materijal	Aluminijum
Dužina (mm)	83
Širina (mm)	83
Visina (mm)	24
Dodatni pribor	LI43319521
Potreban pribor	LID 12102--; LID 12571--
DxŠxV mm	83x83x24
OTVOR mm	Ø75

Dimenzija: Pinta-A MR16 Spot ugaona GU5,3, 50W, IP20, pokretna, bela



83mm



| 83mm |



24mm



Tabela artikla

OPIS	Kat. broj
Pinta-A MR16 Spot ugaona GU5,3, 50W, IP20, pokretna, bela podesivo	LID11048
Potreban pribor	
7304A/W/38, LED MR16 5w 12v WW 38deg	LID12102
Trafo 230V 12VAC 35-105W dimabilni Univerzalni dimer	LID12571
Dodatni pribor	
RL-MR16 35 DIM sijalica 5W 12V 36° 827 350lm 950cd GU5.3	LI43319521