


Tehničke karakteristike artikla: LID12356--

Marra LED traka 14,4W/m 60LEDs/m 1150lm/m 6000K 24VDC IP68 €ECONOMY

LED traka, dimabilna, 5 metara rolna



Tehnički podaci

Vrsta svetiljke (prema načinu primene)	LED traka
Način montaže	Podna Plafonska nadgradna Montaža na zid
Materijal	PVC
Ugao emisije (°)	120
Nazivni napon AC (V)	24
Nazivni napon DC (V)	24
Izvor svetla	SMD LED
Watt/m (W/m)	14,40
Boja svetla	Dnevna svetlost
Temperatura boje (K)	6000
Indeks reprodukcije boje	≥80
Svetlosni fluks (lm/m)	900

Tehnički podaci - nastavak

Životni vek	50.000h
Dimabilno	Da
Klasa zaštite	III
IP stepen zaštite	IP54
Sijalica uključena	Da
DxŠxV mm	5000x12x5

Dimenzija: Marra LED traka 14,4W/m 60LEDs/m 1150lm/m 6000K 24VDC IP68



Tabela artikla

OPIS	Kat. broj
Marra LED traka 14,4W/m 60LEDs/m 1150lm/m 6000K 24VDC IP68 LED traka, dimabilna, 5 metara rolna	LID12356
Dodatni pribor	
Alu. profil 7906/AL+PMMA opalni kvadratni difuzor 2metra Odgovara za LED trake 7820, 7821, 7825, 7830, 7831, 7835, 7820W, 7830W, 7831W, 7835W	LID13861
Trouglasti aluminijumski profil 7908/AL+PC opalni difuzor 2m Odgovara za LED trake 7820, 7821, 7825, 7830, 7831, 7835, 7870, 7875, 7820W, 7830W, 7831W, 7835W	LID13862
Alu. ugradni profil 7912R/AL + PC opalni difuzor, 2 metra Odgovara za LED trake 7820, 7821, 7825, 7830, 7831, 7835, 7870, 7875, 7820W, 7830W, 7831W, 7835W	LID13865
7827, Montažna kopča za 7830W / 7831W	LID13413