


Tehničke karakteristike artikla: LID13536--

Sutil Quadro LED Panel 16W, 3000K, 884lm, 168x168mm, bela

ECONOMY

Tehnički podaci

Otvor (mm)	152x152
Vrsta izvora	LAD panel
Montaža	Zidno ugradno Plafonsko ugradno
Boja	belo
Materijal	Aluminijum
Pokrov	Opal
Ugao emisije (°)	120
Pogonski uređaj	LED drajver
Nazivni napon AC (V)	100-240
Ulazni napon AC (V)	100-240
Izlazni napon DC (V)	23-28
Izlazna struja (A)	0,50
Izvor svetla	SMD LED
Snaga (W)	16

Tehnički podaci - nastavak

Boja svetla	toplo bela
Temperatura boje (K)	3000
Indeks reprodukcije boje	≥80
Lumen (lm)	884
Broj svetiljki	1
Životni vek (h)	30000
Dimabilno	da, opciono sa dimabilnim drajverom
Klasa zaštite	II
IPStepen zaštite	IP40
Klasa energetske efikasnosti	A
Sijalica uključena	da
DxŠxV mm	168x168x20
OTVOR mm	152x152

Dimenzija: Sutil Quadro LED Panel 16W, 3000K, 884lm, 168x168mm, bela




Tabela artikla

OPIS	Kat. broj
Sutil Quadro LED Panel 16W, 3000K, 884lm, 168x168mm, bela	LID13536
Dodatni pribor	
LED Drajver 500mA 16W za Sutil und PLANO, dimabilni	LID13554