

Tehničke karakteristike artikla: LID13608--

Extract LED 25W, 4000K, 1900lm, 60°, IP20, aluminium, bela **ECONOMY**



Tehnički podaci

Otvor (mm)	Ø172
Vrsta izvora	Downlight
Montaža	Plafonsko ugradno
Boja	belo
Materijal	Aluminijum
Proizvođač	06-One Light
Ugao emisije (°)	60
Pogonski uređaj	LED drajver
Nazivni napon AC (V)	100-240
Izvor svetla	COB LED
Grlo	LED Platine
Snaga (W)	25
Boja svetla	Neutralno bela
Temperatura boje (K)	4000
Indeks reprodukcije boje	≥80

Tehnički podaci - nastavak

Lumen (lm)	1900
Broj svetiljki	1
Dimabilno	ne
Klasa zaštite	II
IP stepen zaštite	IP20
Klasa energetske efikasnosti	A
Ugradna dubina (mm)	170
Sijalica uključena	da
ØxV mm	188x150
OTVOR mm	Ø172

Dimenzija: Extract LED 25W, 4000K, 1900lm, 60°, IP20, aluminium, bela




Tabela artikla

OPIS	Kat. broj
Extract LED 25W, 4000K, 1900lm, 60°, IP20, aluminium, bela	LID13608