

Tehničke karakteristike artikla: LID13845--

Sutil Round 2 LED panel 3W, 3000K, 180lm, 120°, IP40, bela **€CONOMY**

Ugradni downlighter, kompletno sa driverom



Detalji artikla

3W slim downlight LED, IP40, ideal for commercial applications such as offices, galleries and showrooms. Supplied with 300mA non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.



Tehnički podaci

Svetlosni flux (lm)	180
Boja svetla	Toplo bela
Temperatura boje (K)	3000
Indeks reprodukcije boje	≥80
Životni vek	30.000h
Dimabilno	Ne
Klasa zaštite	II
IP stepen zaštite	IP40
Vrsta svetiljke (prema načinu primene)	LED panel
Sijalica uključena	Da

Tehnički podaci - nastavak

Broj svetiljki	1
Sijalično grlo	LED štampana ploča
Ugao emisije (°)	120
Sistemska efikasnost (lm/W)	60
Faktor snage	0,6
Snaga (W)	3
Upravljačka oprema (napajanje)	LED drajver
Nazivni napon AC (V)	220-240
Frekvencija (Hz)	50/60
Način montaže	Plafonska ugradna
Otvor (mm)	Ø 70
Ugradna dubina (mm)	50
Opis boje	bela
Materijal	Plastika Akril Liveni aluminijum
Visina (mm)	22
Prečnik (mm)	85
Dodatni pribor	LID 16598--
ØxV mm	85x22
OTVOR mm	Ø 70

Dimenzija: Sutil Round 2 LED panel 3W, 3000K, 180lm, 120°, IP40, bela




Tabela artikla

OPIS	Kat. broj
Sutil Round 2 LED panel 3W, 3000K, 180lm, 120°, IP40, bela Ugradni downlighter, kompletno sa driverom	LID13845
Dodatni pribor	
50W Triac, DALI, Push to DIM & 1-10V LED driver IP20 230V; 23 DRIVERS	LID16598