


Tehničke karakteristike artikla: LID13891--

Aline-M LED downlighter, 13W, 3000K, 925lm, IP54, bela **ECONOMY**

Kupatilski downlighter



Detalji artikla

13W LED recessed downlight, IP54. Suitable for bathroom installations. Supplied with non-dimmable LED 300mA driver. Complies with standard EN60598-1 and any other specific standards.



Tehnički podaci

Tehnički podaci - nastavak

Svetlosni flux (lm)	925
Boja svetla	Toplo bela
Temperatura boje (K)	3000
Indeks reprodukcije boje	≥80
Životni vek	40.000h
Dimabilno	Ne
Klasa zaštite	II
IP stepen zaštite	IP54
Vrsta svetiljke (prema načinu primene)	Plafonska svetiljka ugradna
Sijalica uključena	Da
Broj svetiljki	1
Sijalično grlo	LED štampana ploča
Ugao emisije (°)	90
Sistemska efikasnost (lm/W)	71
Faktor snage	0,9
Snaga (W)	13
Upravljačka oprema (napajanje)	LED drajver
Nazivni napon AC (V)	220-240
Frekvencija (Hz)	50/60
Način montaže	Plafonska ugradna
Otvor (mm)	Ø 95
Ugradna dubina (mm)	70
Opis boje	bela
Materijal	Plastika Liveni aluminijum
Visina (mm)	48
Prečnik (mm)	110
Dodatni pribor	LID 16949--
ØxV mm	110x48
OTVOR mm	Ø 95

Dimenzija: Aline-M LED downlighter, 13W, 3000K, 925lm, IP54, bela



Tabela artikla

OPIS	Kat. broj
Aline-M LED downlighter, 13W, 3000K, 925lm, IP54, bela Kupatilski downlighter	LID13891
Dodatni pribor	
Konektor 32A 2x3-port 26 ACCES&GADGETS	LID16949