


Tehničke karakteristike artikla: LID14068--

Mara-I-R LED 25W 3000K 1800lm, IP54, bela **€CONOMY**

Svetiljka



Kriva prostiranja svetla



Detalji artikla

25W COB LED cylinder, IP54, suitable for indoor and outdoor installation. Complete with non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.



Tehnički podaci

Svetlosni flux (lm)

1800

Tehnički podaci - nastavak

Boja svetla	Toplo bela
Temperatura boje (K)	3000
Indeks reprodukcije boje	≥80
Dimabilno	Ne
Klasa zaštite	I
IP stepen zaštite	IP54
Vrsta svetiljke (prema načinu primene)	Plafonska svetiljka nadgradna
Sijalica uključena	Da
Broj svetiljki	1
Sijalično grlo	LED štampana ploča
Ugao emisije (°)	60
Sistemska efikasnost (lm/W)	72
Faktor snage	0,9
Snaga (W)	25
Upravljačka oprema (napajanje)	LED drajver
Nazivni napon AC (V)	100-240
Ulazni napon AC (V)	100-240
Nazivna struja mA (mA)	600
Frekvencija (Hz)	50/60
Način montaže	Plafonska nadgradna
Opis boje	bela
Materijal	Aluminijum
Visina (mm)	120
Prečnik (mm)	160
Dodatni pribor	LID16949--
ØxV mm	120x160

Dimenzija: Mara-I-R LED 25W 3000K 1800lm, IP54, bela



Tabela artikla

OPIS	Kat. broj
Mara-I-R LED 25W 3000K 1800lm, IP54, bela Svetiljka	LID14068
Dodatni pribor	
Konektor 32A 2x3-port 26 ACCES&GADGETS	LID16949