


Tehničke karakteristike artikla: LID14445--

Mercury 1, 12W, 4000K, 1100lm, 700mA, 40°, IP20, bela **€ECONOMY**

Plafonska ugradna spot svetiljka, dimabilna



Tehnički podaci

Otvor (mm)	Ø75
Montaža	Plafonsko ugradno
Boja	belo
Materijal	Liveni aluminijum
Proizvođač	O6-One Light
Ugao emisije (°)	40
Pogonski uređaj	Bez LED drajvera
Nazivna struja mA (mA)	700
Izvor svetla	LED
Snaga (W)	12
Boja svetla	Neutralno bela
Temperatura boje (K)	4000
Indeks reprodukcije boje	>80
Lumen (lm)	1100

Tehnički podaci - nastavak

Dimabilno	da
Klasa zaštite	III
IP stepen zaštite	IP20
Ugradna dubina (mm)	110
ØxV mm	85x100
OTVOR mm	Ø75

Dimenzija: Mercury 1, 12W, 4000K, 1100lm, 700mA, 40°, IP20, bela



Tabela artikla

OPIS	Kat. broj
Mercury 1, 12W, 4000K, 1100lm, 700mA, 40°, IP20, bela Plafonska ugradna spot svetiljka, dimabilna	LID14445