


Tehničke karakteristike artikla: LID14512--

Zoe Q LED 3W, 3000K, 120lm, 350mA, IP54, bela **ECONOMY**

ugradna zidna svetiljka, bez drivera



Detalji artikla

3W 350mA LED wall recessed light, IP54, ideal for both indoor and outdoor installation. Requires 350mA driver. Supplied with box for concrete installation. Complies with standard EN60598-1 and any other specific standards.



Tehnički podaci

Svetlosni flux (lm)	120
Boja svetla	Toplo bela
Temperatura boje (K)	3000
Indeks reprodukcije boje	≥90
Dimabilno	U zavisnosti od driver-a Da
Klasa zaštite	III
IP stepen zaštite	IP54
Vrsta svetiljke (prema načinu primene)	svetiljke za ugradnju u zid
Sijalica uključena	Da

Tehnički podaci - nastavak

Sijalično grlo	LED štampana ploča
Ugao emisije (°)	24
Sistemska efikasnost (lm/W)	40
Snaga (W)	3
Upravljačka oprema (napajanje)	Mora se poručiti odvojeno
Nazivna struja mA (mA)	350
Ulazna struja (A)	0,35
Način montaže	Zidno ugradno
Otvor (mm)	Ø 49
Ugradna dubina (mm)	110 (zement), 70 (gips)
Opis boje	bela
Materijal	Aluminijum
Dužina (mm)	56
Širina (mm)	56
Visina (mm)	54
Dodatni pribor	LID16949--
Potreban pribor	LID13677--; LID16462--;
DxŠxV mm	56x56x54
OTVOR mm	Ø 49

Dimenzija: Zoe Q LED 3W, 3000K, 120lm, 350mA, IP54, bela




Tabela artikla

OPIS	Kat. broj
Zoe Q LED 3W, 3000K, 120lm, 350mA, IP54, bela ugradna zidna svetiljka, bez drivera	LID14512
Potreban pribor	
89004, DRIVER 350mA 1-4W LED IP66 100-240V 23 DRIVERS	LID13677
LED driver 230V 2-4W 350mA dimabilna 23 DRIVERS	LID16462
Dodatni pribor	
Konektor 32A 2x3-port 26 ACCES&GADGETS	LID16949