


Tehničke karakteristike artikla: LID15114--

Dewy 2 LED 40W 4000K 3200lm 230V IP65 L=1515mm PC/PC siva

IK08, difuzor otporan na vlagu, kompletno sa driverom



Kriva prostiranja svetla



Detalji artikla

IP65 LED fitting to replace T8 IP65 traditional waterproof fluorescent. Stainless steel clips included. Polycarbonate body and diffuser. Supplied with non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.

Tehnički podaci

Svetlosni flux (lm)	4000
Boja svetla	Neutralno bela
Temperatura boje (K)	4000
Indeks reprodukcije boje	≥80

Tehnički podaci - nastavak

Životni vek	30.000h
Dimabilno	Ne
Klasa zaštite	I
IP stepen zaštite	IP65
IK stepen zaštite	IK08
Vrsta svetiljke (prema načinu primene)	Vodonepropusna svetiljka
Sijalica uključena	Da
Sijalično grlo	LED štampana ploča
Sistemska efikasnost (lm/W)	100
Faktor snage	0,9
Snaga (W)	40
Upravljačka oprema (napajanje)	LED drajver
Nazivni napon AC (V)	220-240
Ulazni napon AC (V)	220-240
Nazivna struja mA (mA)	700
Ulazna struja (A)	0,70
Frekvencija (Hz)	50/60
Način montaže	Plafonska nadgradna Montaža na zid
Opis boje	sivo
Materijal	PC
Pokrov	Opal
Dužina (mm)	1515
Širina (mm)	84
Visina (mm)	80
Dodatni pribor	LID 16949--
DxŠxV mm	1515x84x80

Dimenzija: Dewy 2 LED 40W 4000K 3200lm 230V IP65 L=1515mm PC/PC siva



Tabela artikla

OPIS	Kat. broj
Dewy 2 LED 40W 4000K 3200lm 230V IP65 L=1515mm PC/PC siva IK08, difuzor otporan na vlagu, kompletno sa driverom	LID15114
Dodatni pribor	
Konektor 32A 2x3-port 26 ACCES&GADGETS	LID16949