

Tehničke karakteristike artikla: LID15526--

Marra LED traka 4,8W/m, 500lm/m, 4000K, 24VDC, IP20

potreban 24V DC driver



Detalji artikla

Vertical light Flexible LED light strip, with SMD3014 LEDs, 60LEDs/meter, 4,8W/meter. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing. Can be cut every 10cm (6-LED segment). Requires 24V DC constant voltage LED driver. Complies with standard EN60598-1 and any other specific standards.

Tehnički podaci

Boja svetla	Neutralno bela
Temperatura boje (K)	4000
Indeks reprodukcije boje	≥90
Dimabilno	U zavisnosti od driver-a Da
Klasa zaštite	III
IP stepen zaštite	IP20
Vrsta svetiljke (prema načinu primene)	LED traka
Sijalica uključena	Da
Sijalično grlo	LED štampana ploča
Sistemska efikasnost (lm/W)	104
Upravljačka oprema (napajanje)	Mora se poručiti odvojeno

Tehnički podaci - nastavak

Nazivni napon DC (V)	24
Ulazni napon DC (V)	24
Način montaže	Podna Plafonska nadgradna Montaža na zid
Dodatni pribor	LID12346--; LID12344--;
Svetlosni fluks (lm/m)	500

Dimenzija: Marra LED traka 4,8W/m, 500lm/m, 4000K, 24VDC, IP20

Cut every 10cm
(6-LED segment)



Tabela artikla

OPIS	Kat. broj
Marra LED traka 4,8W/m, 500lm/m, 4000K, 24VDC, IP20 potreban 24V DC driver	LID15526
Dodatni pribor	
7824, LED POWER SUPPLY CABLE za 7820 / 7821 Svetiljka	LID12346
7822, LED STRIP konektor za 7820 / 7821 08 STRIPS & PROFILES	LID12344