

Tehničke karakteristike artikla: LID17788--

Svetiljka Linear BU 20-40W 3K/4K/5K CRI90 IP20 UGR17 bela

Direct (20/30/40W) 34° / indirect (16/20/25W) 120°, 3m kabla



Detalji artikla

CCT and Power variable 40W UGR17 Linear system with 48 LED spots and uplight for suspended installation, ideal for offices. Complete with 2 x power variable drivers. Complies with standard EN60598-1 and any other specific standards.

Tehnički podaci

Neto dužina (mm)	1.300,00
Neto širina (mm)	35,00
Neto visina (mm)	70,00
Opis boje	bela
Materijal	Aluminijum
Ugao emisije (°)	34/120
Faktor odsjaja (UGR)	<17
Upravljačka oprema (napajanje)	LED drajver
Nazivni napon AC (V)	220-240
Ulazni napon AC (V)	220-240
Sijalično grlo	LED štampana ploča
Sistemska efikasnost (lm/W)	95

Tehnički podaci - nastavak

Snaga (W)	40 30 20
Boja svetla	Neutralno bela Toplo bela Hladno bela
Temperatura boje (K)	5000 4000 3000
Indeks reprodukcije boje	≥90
Svetlosni flux (lm)	max. 1800/3800
Dimabilno	Ne
Klasa zaštite	I
IP stepen zaštite	IP20
Prečnik (mm)	68
DxŠxV mm	1300x35x70

Dimenzija: Svetiljka Linear BU 20-40W 3K/4K/5K CRI90 IP20 UGR17 bela



OPIS	Kat. broj
Svetiljka Linear BU 20-40W 3K/4K/5K CRI90 IP20 UGR17 bela	LID17788
Direct (20/30/40W) 34° / indirect (16/20/25W) 120°, 3m kabla	