


Tehničke karakteristike artikla: LIG3100007

SEGON Downlighter 24W ED 2500lm/3000K MAT IP44 70° bela

ugradni downlighter



Kriva prostiranja svetla




Tehnički podaci

Neto visina (mm)	140,00
Neto prečnik (mm)	240,00
Neto težina (kg)	0,70
Min. temperatura okoline (°C)	0
Maks. temperatura okoline (°C)	35

Tehnički podaci - nastavak

Otvor (mm)	Ø215
Vrsta svetiljke (prema načinu primene)	Plafonska svetiljka ugradna
Način montaže	Plafonska ugradna
Opis boje	bela
Materijal	Aluminijum
Pokrov	Mat
Ugao emisije (°)	70
Upravljačka oprema (napajanje)	LED drajver
Nazivni napon AC (V)	220-240
Sijalično grlo	LED Platine
Sistemska efikasnost (lm/W)	104
Snaga (W)	24
Boja svetla	Toplo bela
Temperatura boje (K)	3000
Indeks reprodukcije boje	≥80
Svetlosni flux (lm)	2500
Životni vek	50.000h / L80 / B10
Dimabilno	Ne
Klasa zaštite	I
IP stepen zaštite	IP44
IK stepen zaštite	IK07
Sijalica uključena	Da
Prečnik (mm)	240
ØxV mm	240x140
OTVOR mm	Ø215

Dimenzija: SEGON Downlighter 24W ED 2500lm/3000K MAT IP44 70° bela



OPIS

Kat. broj

SEGON Downlighter 24W ED 2500lm/3000K MAT IP44 70° bela
ugradni downlighter

LIG3100007