




Tehničke karakteristike artikla: LIH0000080

Rundo Round nadgradna 4x24W T16+2x24W TC-L ECG, eloksirana



Tehnički podaci

Vrsta izvora	Plafonska svetiljka nadgradna Svetiljka privezak
Montaža	Plafonsko nadgradna Viseće
Boja	eloksirano
Materijal	Aluminijum
Pokrov	Opal
Pogonski uređaj	EVG
Nazivni napon AC (V)	230
Prečnik (mm)	650
Izvor svetla	Fluorescenta sijalica Ø16mm
Grlo	G5
Snaga (W)	4x24+2x24
Broj svetiljki	4+2
Klasa zaštite	I

Tehnički podaci - nastavak

IPStepen zaštite	IP20
ØxV mm	650x70

Dimenzija: Rundo Round nadgradna 4x24W T16+2x24W TC-L ECG, eloksirana




Tabela artikla

OPIS	Kat. broj
Rundo Round nadgradna 4x24W T16+2x24W TC-L ECG, eloksirana	LIH0000080
Dodatni pribor	
Okrugla fluo cev T16-R 22W/840 2G13	LI5W528465
Okrugla fluo cev T16-R 40W/840 2G13	LI5W528526
Set za kačenje za Round +transp.kabel 4x0, 75mm L-2000mm	LIH0000075
Distancer za Rundo Round Ø 450 do 650mm	LIH0000102