




Tehničke karakteristike artikla: LIH0000082

Rundo Round 1x22W T16-R+1x40W T16-R

DALI, eloksirana



Tehnički podaci

Vrsta izvora	Plafonska svetiljka nadgradna Svetiljka privezak
Montaža	Plafonsko nadgradna Viseće
Boja	eloksirano
Materijal	Aluminijum
Pokrov	Opal
Pogonski uređaj	EVG
Nazivni napon AC (V)	230
Izvor svetla	Prsten Ø16mm
Grlo	2GX13
Snaga (W)	22+40
Broj svetiljki	1+1
Dimabilno	DALI
Klasa zaštite	I

Tehnički podaci - nastavak

Stepen zaštite	IP20
ØxV mm	370x70

Dimenzija: Rundo Round 1x22W T16-R+1x40W T16-R DALI, eloksirana



Tabela artikla

OPIS	Kat. broj
Rundo Round 1x22W T16-R+1x40W T16-R DALI, eloksirana	LIH0000082
Dodatni pribor	
Okrugla fluo cev T16-R 22W/840 2G13	LI5W528465
Okrugla fluo cev T16-R 40W/840 2G13	LI5W528526
Set za kačenje za Round+transp.kabel 5x0, 75mm L-2000mm	LIH0000077
Odstojnik za Rundo Round Ø 370mm i Rundo Square	LIH0000103