


Tehničke karakteristike artikla: LIH0000099

Rundo Round PL 4x24W T16+2x24W TC-L DALI, eloksirana



Tehnički podaci

Vrsta izvora	Svetiljka privezak
Montaža	Viseće
Boja	eloksirano
Materijal	Aluminijum
Pokrov	Opal
Pogonski uređaj	EVG
Nazivni napon AC (V)	230
Izvor svetla	Fluorescenta sijalica Ø16mm Fluokompaktna sijalica
Grlo	G5
Snaga (W)	4x24+2x24
Broj svetiljki	4+2
Dimabilno	DALI
Klasa zaštite	I
Stepen zaštite	IP20

Tehnički podaci - nastavak

ØxV mm

650x70

Dimenzija: Rundo Round PL 4x24W T16+2x24W TC-L DALI, eloksirana




Tabela artikla

OPIS	Kat. broj
Rundo Round PL 4x24W T16+2x24W TC-L DALI, eloksirana	LIH0000099
Dodatni pribor	
Okrugla fluo cev T16-R 22W/840 2G13	LI5W528465
Okrugla fluo cev T16-R 40W/840 2G13	LI5W528526
Set za kačenje za Round+transp.kabel 5x0, 75mm L-2000mm	LIH0000077
Distancer za Rundo Round Ø 450 do 650mm	LIH0000102