

Tehničke karakteristike artikla: LIMQ1E805A

M48 Area QU-D 1 Modul 48LEDs 4000K IP66 114W 10775lm RAL9006

Version with 1 Module 48LEDs - SK.II - Power of luminaire 114W with Lumen output 10.775lm @700mA, Power of luminaire 83W with lumen output 8.615lm @525mA, Power of luminaire 55W with lumen output 6.215lm @350mA - "Economy" Version (ON-OFF)



Tehnički podaci

Vrsta izvora	Reflektor za hale
Montaža	Plafonsko nadgradna Viseće
Boja	RAL 9006 (siva)
Materijal	Aluminijum
Pogonski uređaj	LED drajver
Nazivni napon AC (V)	230
Izvor svetla	LED
Grlo	LED Platine
Snaga (W)	114
Boja svetla	Neutralno bela
Temperatura boje (K)	4000
Indeks reprodukcije boje	≥70
Lumen (lm)	10775

Tehnički podaci - nastavak

Broj svetiljki	1
Klasa zaštite	II
Stepen zaštite	IP66
Sijalica uključena	da
DxŠxV mm	495x175x65

Tabela artikla

OPIS	Kat. broj
M48 Area QU-D 1 Modul 48LEDs 4000K IP66 114W 10775lm RAL9006 Version with 1 Module 48LEDs - SK.II - Power of luminaire 114W with Lumen output 10.775lm @700mA, Power of luminaire 83W with lumen output 8.615lm @525mA, Power of luminaire 55W with lumen output 6.215lm @350mA - "Economy" Version (ON-OFF)	LIMQ1E805A
Dodatni pribor	
Plafonski nosač za M48 Area RAL9006	LI06MQ900A
Pribor za vešanje M48 dužina 1,5m	LI06MQ901J