

Tehničke karakteristike artikla: LIMQ1L605A

M48 Area QU-D 2Modula 96LEDs 4000K IP66 227W 21545lm RAL9006

Version with 2 Modules 96LEDs - SK.II - Power of luminaire 227W with Lumen output 21.545lm @700mA, Power of luminaire 166W with Lumen output 17.225lm @525mA, Power of luminaire 109W with Lumen output 12.425lm @350mA - "Economy" Version (ON-OFF)



Tehnički podaci

Vrsta izvora	Reflektor za hale
Montaža	Plafonsko nadgradna Viseće
Boja	RAL 9006 (siva)
Materijal	Aluminijum
Pogonski uređaj	LED drajver
Nazivni napon AC (V)	230
Izvor svetla	LED
Grlo	LED Platine
Snaga (W)	227
Boja svetla	Neutralno bela
Temperatura boje (K)	4000
Indeks reprodukcije boje	≥70
Lumen (lm)	21545

Tehnički podaci - nastavak

Broj svetiljki	2
Klasa zaštite	II
Stepen zaštite	IP66
Sijalica uključena	da
DxŠxV mm	495x340x65

Tabela artikla

OPIS	Kat. broj
M48 Area QU-D 2Modula 96LEDs 4000K IP66 227W 21545lm RAL9006	
Version with 2 Modules 96LEDs - SK.II - Power of luminaire 227W with Lumen output 21.545lm @700mA, Power of luminaire 166W with Lumen output 17.225lm @525mA, Power of luminaire 109W with Lumen output 12.425lm @350mA - "Economy" Version (ON-OFF)	LIMQ1L605A
Dodatni pribor	
Plafonski nosač za M48 Area RAL9006	LI06MQ900A
Pribor za vešanje M48 dužina 1,5m	LI06MQ901J