


Tehničke karakteristike artikla: MGC56160--

Strujni transformator 1600/5A, 60x30mm, klasa 0.5

Ulazna struja 1600A, Teret Klasa 0.5 (10VA)




Tehnički podaci

IP stepen zaštite	IP20
Teret	Klasa 0.5 (10VA)
Objava	Due to dangerous overvoltage and overheating, the Current Transformer is not allowed to be operated with open secondary Side. (EN 60044-1 /A2) As soon as the Measurement Device, the Energy Counter or the Net Analyzer is disconnected, the secondary Side has to be shortcuted!
Svrha upotrebe	za bakarne šine do 50 x 30 mm za bakarne šine do 60 x 10 mm
Standard proizvoda	EN 61869-2
Otvor (mm)	50x30 / 60x10
Zahtevi za izolaciju	
Maks. radni napon Um	0.72kV r.m.s.
Ispitni napon izolacije	3 kV R.M.S. 50 Hz/1 min
Izolacija	Klasa B (EN/IEC 61869-1, 61869-2)
Specifikacije	
Nazivna struja primarne strane Ipr (A)	1600

Tehnički podaci - nastavak

Nazivna frekvencija (Hz)	50-60Hz
Kratkotrajna struja Ith	< 60Ipr
Termička nazivna stalna struja prema EN60044-1	
Nazivna dinamička struja Idyn	2.5Ith
Nazivna struja sekundarne strane Isr	5A
Moment zatezanja (Nm)	2
Materijal kućišta	Polycarbonate, self-extinguishing
Klase tačnosti	
Referentna temperatura (°C)	23°C ±1°C
Greška struje opterećenja	Za klasu 0.5 i 20% In: ±0.75%
	Za klasu 0.5 i 120% In: ±0.5%
	Za klasu 0.5 i 100% In: ±0.5%
	Za klasu 0.5 i 5% In: ±1.5%
Radni uslovi	
Temperaturni okvir - Transport/skladištenje (°C)	-25 to +60
Temperaturni okvir - Operativni (°C)	-5 do +40

Maßbild MGC56160--



OPIS

Strujni transformator 1600/5A, 60x30mm, klasa 0.5

Ulazna struja 1600A, Teret Klasa 0.5 (10VA)

Kat. broj

MGC56160