

Emergency luminaire KW Autotest LED 3h 230V AC ceiling

1h/3h adjustable, ceiling surface mounting with pictograms on one or two sides or for wall surface mounting with pictogram on one side, viewing distance: 16m, IP54, protection class II, 1h: 300lm; 3h: 300lm



Tehnički podaci


Neto dužina (mm)	390,00
Neto širina (mm)	93,00
Neto visina (mm)	139,00
Neto težina (kg)	1,30
Vrsta svetiljke (prema načinu primene)	anti-panik svetiljka
VB-CPS	Sa sopstvenom baterijom
Funkcija	samokontrola
Verzija	Plastične svetiljke
Dizajn	KW
Bezhalogeni	Plastično kućište, bez halogena
Opis boje	bela
Područje prepoznavanja/domet (m)	16

Tehnički podaci - nastavak

Vreme autonomije (h)	3
Izvor svetla	LED (3W)
Lumen	1h: 300;3h: 300
Opseg napona (V)	230V AC 50Hz ±20%
Baterije (V/Ah)	2x 3,2V/1,6Ah LiFePO4
IP stepen zaštite	IP54
Način montaže	Plafonska nadgradna
Min. temperatura okoline (°C)	-5
Maks. temperatura okoline (°C)	40
AA Klasa E 8101	AA4
Proizvođač	Schrack

Dimenzija: Emergency luminaire KW Autotest LED 3h 230V AC ceiling

NLKWD...



Abstandstabelle 1h, 3h Autonomie - Min. Beleuchtungsstärke: 1lx - Wartungsfaktor 0,80

Montagehöhe [m]					
2,00	3,55	9,23	8,09	7,02	2,74
2,50	3,68	9,78	8,62	7,52	2,84
3,00	3,72	10,17	8,98	7,85	2,86
3,50	3,66	10,40	9,20	8,05	2,79
4,00	3,51	10,51	9,29	8,11	2,61
5,00	2,80	10,34	9,08	7,86	1,84

Tabela artikla

OPIS	Kat. broj
Emergency luminaire KW Autotest LED 3h 230V AC ceiling 1h/3h adjustable, ceiling surface mounting with pictograms on one or two sides or for wall surface mounting with pictogram on one NLKWD401SC side, viewing distance: 16m, IP54, protection class II, 1h: 300lm; 3h: 300lm	
Dodatni pribor	
Zaštitna rešetka za seriju KW	NLBKW
Par cevnih nosača 500mm beli, montaža plafon, ožičeni	NL2PW
Zidni nosač beli pogodan za: KB, KX, KW, KCD, KE, GX, RX	NLAWX001