

Tehničke karakteristike artikla: NLPXW438WL

PX protivpanična svetiljka WirelessControl

4x1W ERT-LED 8h

Izlazni znak zidni / protivpanična plafonska, 30m, radio, LiFePO₄, 245lm



Tehnički podaci

Neto dužina (mm)	340,00
Neto širina (mm)	60,00
Neto visina (mm)	170,00
Neto težina (kg)	0,90
Vrsta svetiljke (prema načinu primene)	anti-panik svetiljka sigurnosna rasveta
VB-CPS	Sa sopstvenom baterijom
Funkcija	Wireless kontrola Professional
Verzija	Plastične svetiljke
Dizajn	PX
Bezhalogeni	Bez halogeno plastično kućište
Opis boje	RAL 9003 (bela)
Piktogram	Slide-in pictogram set (2x man in the door and one arrow that can be rotated by 90°) included in accordance with ISO 7010

Tehnički podaci - nastavak

Područje prepoznavanja/domet (m)	30
Vreme autonomije (h)	3
Izvor svetla	ERT-LED (4W)
Lumen	245
Opseg napona (V)	230V AC 50Hz ±20%
Power maintained mode (W)	5,70
Power non-maintained mode (W)	0,80
Power max. (W)	7,50
Baterije (V/Ah)	2x 3,2V/3,3Ah LiFePO4
IP stepen zaštite	IP65
Otpornost na udar	IK05
Način montaže	Stropna ugradna opcija Univerzalna Plafonska nadgradna Montaža na zid
Min. temperatura okoline (°C)	-5
Maks. temperatura okoline (°C)	40
AA Klasa E 8101	AA4
Proizvođač	Schrack

Spacing table with square lens (for optimized illumination of the pictogram) (included in scope delivery) - Minimum illuminance on the centerline at +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 8h

					
2,00	4,29	9,95	9,95	9,95	4,29
2,50	4,55	11,35	11,35	11,35	4,55
3,00	4,29	12,42	12,42	12,42	4,29
3,50	3,11	12,87	12,87	12,87	3,11
4,00	2,16	12,25	12,25	12,25	2,16

Spacing table with corridor lens (NLLSYSF4 must be ordered separately) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 8h

					
2,00	4,93	10,84	8,98	7,23	2,84
2,50	5,84	13,01	10,28	7,84	2,97
3,00	6,67	14,99	11,54	8,22	3,03
3,50	7,22	16,82	12,58	8,48	2,99
4,00	5,37	18,52	13,5	8,63	2,94
5,00	3,93	17,81	11,74	8,46	2,8
6,00	2,21	16,25	10,3	8,3	2,25

Spacing table with round lens (NLLSYSR4 must be ordered separately) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 8h

					
2,00	3,89	8,38	8,38	8,38	3,89
2,50	4,58	10,05	10,05	10,05	4,58
3,00	5,19	11,54	11,54	11,54	5,19
3,50	5,15	12,91	12,91	12,91	5,15
4,00	3,83	13,42	13,42	13,42	3,83
5,00	1,54	12,54	12,54	12,54	1,54

Spacing table with spot lens (NLLSYSS4 must be ordered separately) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 8h

					
2,00	1,91	4,79	4,79	4,79	1,91
2,50	2,31	5,8	5,8	5,8	2,31
3,00	2,53	6,08	6,08	6,08	2,53
3,50	2,78	6,57	6,57	6,57	2,78
4,00	3,02	7,04	7,04	7,04	3,02
5,00	3,41	7,99	7,99	7,99	3,41
6,00	3,75	8,91	8,91	8,91	3,75
7,00	3,98	9,64	9,64	9,64	3,98
8,00	4,1	10,37	10,37	10,37	4,1
9,00	4,12	10,93	10,93	10,93	4,12
10,00	4,05	11,34	11,34	11,34	4,05
12,00	3,59	11,7	11,7	11,7	3,59
14,00	2,56	11,53	11,53	11,53	2,56

Spacing table with high corridor lens (NLLSYSH4 must be ordered separately)
- Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 -
Autonomy time 8h

					
2,00	2,2	5,84	7,56	9,25	4,02
2,50	2,27	6,2	8,38	10,56	4,66
3,00	2,27	6,4	9,19	11,98	5,22
3,50	2,19	6,5	9,87	13,25	5,61
4,00	1,95	6,5	10,45	14,4	5,95
5,00	1,77	6,28	11,23	16,18	6,41
6,00	1,83	5,31	11,34	17,46	6,67
7,00	1,81	5,01	11,53	18,35	6,6
8,00	1,81	5,17	11,54	18,98	6,12
9,00	1,73	5,14	10,85	19,27	5,89
10,00	1,58	5,13	10,53	18,88	5,61
12,00	1,02	5,05	9,65	17,18	3,55

Tabela artikla

OPIS	Kat. broj
PX protivpanična svetiljka WirelessControl 4x1W ERT-LED 8h Izlazni znak zidni / protivpanična plafonska, 30m, radio, LiFePO4, 245lm	NLPXW438WL
Dodatni pribor	
Poklopac za zaštitu od kiše za KC , pleksi	NLKCRD
Zaštitna rešetka za serije KC, KX, PF, LX, RX l x h x d: 450 x 280 x 125mm	NLBALL2
Piktogram set NLPX 2x kolica 2x dijagonalne 2-delni piktogrami, vidljivost: 30m	NLPXPIKTO2
	NLTESTSC2
Zaštitni poklopac za test dugme NLTEST2 39	NLTEST2COV
Set od 2 bat. 3.2V 3.3Ah LiFePO4 bež. Kontrol. Svet. sa LEO LifePO4 - Litijum metalna fosfatna baterija, UN3480- UN 3480: Litijum jonska baterija	NLAKKU323L