

Tehničke karakteristike artikla: QLFGP1000-

Switch 8xRJ45 10/ 100 (PoE) + 1xRJ45 + 1xSFP 1000

8 x 10/100Base-TX RJ45 PoE (802.3af) Ports, 1 x 10/100/1000Base-T RJ45 Port, 1 x 100/1000Base-X SFP utor



SCHRACK-Info

QLFGP1000- is a 8-port 10/100Mbps Fast Ethernet Switch with Power over Ethernet (PoE) capability. With 8 dip switches, each PoE port can be manually set for On-Off control.

QLFGP1000- supports up to 30W on each LAN port when the DIP switch is in the ON position.

Using a PoE repeater, it is possible to extend the connection a further 100 meters, or even daisy-chain several PoE repeaters together for greater distances Dual 10/100Mbps ports can connect with other edge switches or NVR as uplink ports.

Key-Features

- 8 Fast Ethernet PoE ports, 1 Gigabit port and 1 Gigabit SFP slot
- PoE on/off control per port by dip switches
- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- Simple Plug and Play installation

TECHNICAL DATA

- Approval and compliance
 - FCC, CE, RoHS
- Max. operating humidity
 - 90%

- Max. operating temperature
 - 45C°
- Max. storage humidity
 - 90%
- Max. storage temperature
 - 70C°
- Min. operating humidity
 - 10%
- Min. operating temperature
 - -40°
- Backplane
 - 10/100/1000Mbps
- Indicators
 - Power, Active, 10/100/1000M, PoE
- MAC address table
 - 4K
- Flash memory size
 - 512
- Mount
 - Desk mount
- Standards
 - IEEE 802.3 10-BASE-T, Ethernet
 - IEEE 802.3u 100-BASE-TX, Fast Ethernet
 - IEEE 802.3ab 1000BASE-T, Gigabit Ethernet
 - IEEE 802.3x Full-duplex Flow Control
 - IEEE 802.3 10-BASE-T, Ethernet
 - IEEE 802.3u 100-BASE-TX, Fast Ethernet
 - IEEE 802.3ab 1000BASE-T, Gigabit Ethernet
 - IEEE 802.3x Full-duplex Flow Control
 - IEEE 802.3 10-BASE-T, Ethernet
 - IEEE 802.3u 100-BASE-TX, Fast Ethernet
 - IEEE 802.3ab 1000BASE-T, Gigabit Ethernet
 - IEEE 802.3x Full-duplex Flow Control
 - IEEE 802.3 10-BASE-T, Ethernet
 - IEEE 802.3u 100-BASE-TX, Fast Ethernet
 - IEEE 802.3ab 1000BASE-T, Gigabit Ethernet
 - IEEE 802.3x Full-duplex Flow Control
 - IEEE 802.3 10-BASE-T, Ethernet
 - IEEE 802.3u 100-BASE-TX, Fast Ethernet

- IEEE 802.3ab 1000BASE-T, Gigabit Ethernet
- IEEE 802.3x Full-duplex Flow Control
- IEEE 802.3 10-BASE-T, Ethernet
- IEEE 802.3u 100-BASE-TX, Fast Ethernet
- IEEE 802.3ab 1000BASE-T, Gigabit Ethernet
- IEEE 802.3x Fullduplex Flow Control
- IEEE 802.3 10-BASE-T, Ethernet
- IEEE 802.3u 100-BASE-TX, Fast Ethernet
- IEEE 802.3ab 1000BASE-T, Gigabit Ethernet
- IEEE 802.3x Full-duplex Flow Control
- IEEE 802.3 10-BASE-T, Ethernet
- IEEE 802.3u 100-BASE-TX, Fast Ethernet
- IEEE 802.3ab 1000BASE-T, Gigabit Ethernet
- IEEE 802.3x Full-duplex Flow Control
- Product weight
 - 1,5 kg
- Product breadth
 - 188 mm
- Product depth
 - 118
- Product height
 - 38 mm
- Color
 - Grey
- EAN
 - 4015867187982
- Model number
 - QLFGP1000-
- Fast Ethernet multi-mode ST
 - 1
- Gigabit RJ45/SFP combo
 - 1
- 802.3af/at PoE
 - 8
- Switching capacity
 - 5.6 Gbps
- Grade
 - Commercial

- Data Rate
 - Fast and Gigabit Ethernet
- PoE Supported
 - Yes
- Manageable
 - No
- Fanless
 - Yes
- Concurrent ports
 - Total 10.00
- PoE Power Budget
 - Total 120.00

Package contents

- QLFGP1000-
- Power Adapter
- User Manual

Tehnički podaci

Neto širina (mm)	188,00
Neto visina (mm)	38,00
Neto dubina (mm)	118,00
EAN	4015867187982
Min. temperatura okoline (°C)	0
Maks. temperatura okoline (°C)	70
Proizvod	Ethernet Switch
Brzina	10/100Mbps + 10/100/1000 Uplinks
Portovi	9
Način montaže	Desktop

Tabela artikla

OPIS	Kat. broj
Switch 8xRJ45 10/100 (PoE) + 1xRJ45 + 1xSFP 1000	
8 x 10/100Base-TX RJ45 PoE (802.3af) Ports, 1 x 10/100/1000Base-T RJ45 Port, 1 x 100/1000Base-X SFP utor	QLFGP1000
Dodatni pribor	
Patch kabl RJ45, Cat.6, S/FTP, PVC, sivi, 0,5m	H6GLG00K5G
Patch kabl RJ45, Cat.6, S/FTP, PVC, sivi, 1m	H6GLG01K0G
Patch kabl RJ45, Cat.6, S/FTP, PVC, sivi, 2m	H6GLG02K0G
Patch kabl RJ45, Cat.6, S/FTP, PVC, sivi, 3m	H6GLG03K0G
Patch kabl RJ45, Cat.6, S/FTP, PVC, sivi, 5m	H6GLG05K0G
Patch kabl RJ45, Cat.6, S/FTP, PVC, sivi, 10m	H6GLG10K0G
Patch kabl RJ45, Cat.6, S/FTP, PVC, sivi, 20m	H6GLG20K0G