

Tehničke karakteristike artikla: QLIES0820-

Preklopnik za DIN nosač 8xRJ45 10/ 100 Mbps, bez napajanja

napon napajanja 12VDC-56VDC



SCHRACK-Info

The industrial 8 port Ethernet switch is equipped with 8 port 10/100Mbps Ethernet ports. It is designed for 12-56VDC input sources, especially for IP surveillance, traffic monitoring and for a broad range of applications. It can be used as a stand-alone device for buses, trucks and other vehicles for Surveillance purposes. It is being rigorously tested for your Security, Transportation and Telco application.

Key-Features

- Provides flexibility of 8 x 10/100BASE-TX ports
- Offers DIN rail or panel mounting
- Operating temperature range of -40°C to 75°C
- Supports 12 to 56 VDC power inputs
- Redundant power inputs with terminal block

TECHNICAL DATA

- Approvals and conformity
 - FCC Part 15 Subpart B Class A, CE, VCCI, IEC EN60950-1, IEC 60068-2-27, IEC 60068-2-6
- Max. Operating Humidity
 - 95%
- Max. Operating Temperature

- 75°C
- Min. Operating Humidity
 - 5%
- Min. Operating Temperature
 - -40°C
- Backplane (Gbps)
 - 1.6 Gbit/s
- Indicators
 - PW1(Power 1) Green
 - PW2(Power 2) Green
 - SW(relay) Amber
 - TX/RJ-45 port: LNK (Link/Active) Green
- MAC Address Table
 - 1K
- Mount
 - DIN rail mount
- Output voltage
 - Relay outputs with current carrying capacity of 1 A @24VDC
- Power supply
 - Optional
- Standards
 - IEEE 802.3 10Base-T Ethernet
 - IEEE 802.3u 100Base-TX Fast Ethernet
 - IEEE802.3x Flow Control and Back Pressure
- Product weight
 - 0,73 kg
- Product width
 - 142 mm
- Product depth
 - 105 mm
- Product height
 - 36,2 mm
- Color
 - Black
- EAN
 - 4015867181546
- Model number
 - QLIES0820-
- PoE Supported
 - None

- Concurrent ports
 - 8.00 Total
- Energy consumption
 - 3W @ 48VDC full load

Package Contents

- QLIES0820-
- Wall-Mounting set
- DIN rail mounting set
- High current terminal block

Tehnički podaci

Neto širina (mm)	142,00
Neto visina (mm)	36,20
Neto dubina (mm)	105,00
EAN	4015867181546
Min. temperatura okoline (°C)	-40
Maks. temperatura okoline (°C)	75
Proizvod	Ethernet Switch
Brzina	10/100Mbps
Portovi	8
Način montaže	DIN šina

Tabela artikla

OPIS	Kat. broj
Preklopnik za DIN nosač 8xRJ45 10/100 Mbps, bez napajanja napon napajanja 12VDC-56VDC	QLIES0820
Dodatni pribor	
TOOLLESS LINE - Nosač RJ45 modula (SFA, SFB) za DIN šinu Lightgrey	HSERH010GS
Industrijsko napajanje, 24VDC, 30W, DIN-Rail	QLPOW2410
Industrijsko napajanje, 24VDC, 60W, DIN-Rail	QLPOW2420
Industrijsko napajanje, 24VDC, 75W, DIN-Rail	QLPOW2430
Industrijsko napajanje, 24VDC, 120W, DIN-Rail	QLPOW2440
Industrijsko napajanje, 48VDC, 120W, DIN-Rail napajanje preko PoE	QLPOW4840
Industrijsko napajanje, 48VDC, 240W, DIN-Rail napajanje preko PoE	QLPOW4850
Industrijsko napajanje, 48VDC, 480W, DIN-Rail napajanje preko PoE	QLPOW4860
Napajanje, 110V-240VAC 50/60Hz ; 48VDC/1.35A, 64,8W	QLPOW4801